



Masterpiece Technology (International) Co. Limited

Room 402, Building C, BaiFuHui Industrial Zone, JingLong Jianshe Road East, Longhua

District Shenzhen City, P.R.China Post Code 518109

Tel: +86-755-25174100

Fax: +86-755-25174110

e-Mail: sales@mptic.com

Website: www.mptic.com

MP-8002 (Thermal Bluetooth Receipt Printer)



It is powerful receipt printer with Multi-functional Display Screen (can be shown the capacity of battery, the status of blue tooth connection, the status of printing, Paper out warning, the version of printer)

It applies to mobile products matching use, and suited to outdoor work environments.

The feature has small size, light weight, reliable performance, easy to connect、easy to use.

Applications:

The mobile police system

The tobacco distribution system

The utility meter reading system

The mobile office / mobile logistics systems

The portable instrumentation

The testing equipment, ancillary equipment.

Low operating costs (no ribbons, ink cartridges)

Weight: about 520g (including accessories: lithium-ion batteries, cable, test paper)

Size: 105*100*45mm

Bluetooth transmission distance : Maximum blue tooth communication distance is 10m

Hong Kong office

Tel: +852-63268065
Fax: +852-63268065

Shenzhen office

Tel: +86-755-25174100
Fax: +86-755-25174110

Chengdu office

Tel: +86-28-85432305
Fax: +86-28-85453557

Chongqing office

Tel: +86-23-68638225
Fax: +86-23-68635822

Vancouver office

Tel: +1-778-9183018
Fax: +1-778-9183018



Masterpiece Technology (International) Co. Limited

Room 402, Building C, BaiFuHui Industrial Zone, JingLong Jianshe Road East, Longhua

District Shenzhen City, P.R.China Post Code 518109

Tel: +86-755-25174100

Fax: +86-755-25174110

e-Mail: sales@mptic.com

Website: www.mptic.com

Printing Method	Line Thermal printing
Print speed	<90mm/sec
Reliability TPH Life	100km
Resolution	203DPI (8dot/mm)
Printing Width	72mm (576dot)
Paper Width	79±01mm
Roll Diameter	φ≤40mm
Paper Type	Thermal Paper
Power supply (optional)	rechargeable lithium batteries
Battery	Lithium: 7.4VDC/2000mA,
Charging mode	DC 9V/1.5A-2A
Emulation	ESC/POS/STAR command
Interface	Standard RS232/USB, Bluetooth 2.0/SPP agreement or infrared/IRCOMM agreement (optional).
Working Temperature	-10~50℃
Humidity	10~90%
Language	Support multiple languages
Print parameters	support to download the Logo trademark

Character size: 384 dots/line

Font A: 12*24dots, 1.5(W)*3.0(H)mm

Font B: 9*17dots, 1.1(W)*2.1(H)mm

Simplified/Traditional: 24*24dots,3.0(W)*3.0(H)mm

Printing Chinese character: Chinese: simplified Chinese 24x24 point. support 18030 font library, support Taiwan and HK traditional(complex font)

ANK: ANK characters

Extended character table:

OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/OEM866/OEM852/OEM858/IranII/Latvian/Arabic/PT151,1251/OEM747/WPC1257/Vietnam/OEM864/Hebrew/WPC1255/Thai

Hong Kong office

Tel: +852-63268065
Fax: +852-63268065

Shenzhen office

Tel: +86-755-25174100
Fax: +86-755-25174110

Chengdu office

Tel: +86-28-85432305
Fax: +86-28-85453557

Chongqing office

Tel: +86-23-68638225
Fax: +86-23-68635822

Vancouver office

Tel: +1-778-9183018
Fax: +1-778-9183018