



Waterproof Level	Power	Images			Plug Type	Input Voltage	Output Voltage Range	Max. Current	Safety Approval	Safety Standard	PF	Size(L*W*H)(mm)
IP44	24W (24G Version)				US	100-240VAC	9V-24V	2A max	ETL,FCC	ETL UL1310,FCC Part 15	PF about0.4-0.5	80.03*42.2*30.95 mm
IP44	24W (24GH Version)				EU	200-240VAC	9V-24V	2A max	CE/EMC,LVD	EN 61347-1:2015/A1:2021; EN 61347-2-13:2014+A1:2017; EN IEC55015:2019/+A11:2020;	PF≥0.8	80.03*42.2*30.95 mm
					UK							
IP44	36W (36G Version)				US	100-240VAC	8V-24V	3.5A max	FCC,DOE,CEC(12V 3A)	ETL UL1310,FCC Part 15	PF about0.4-0.5	95.0*51.0*34.1mm
IP44	36W (36GH Version)				EU	200-240VAC	12V-42V	3A max	CE/EMC,LVD,UKCA	EN 61347-1:2015/A1:2021; EN 61347-2-13:2014+A1:2017; EN IEC55015:2019/+A11:2020;	PF≥0.9	99.7*51.6*34.0mm
					UK							
IP44	48W (48BH Version)				EU	200-240VAC	8V-24V	4A max	CE/EMC,LVD	EN IEC 55015:2019+A11:2020; EN 61347:2009;EN 61347-2-13:2014+A1:2017;EN 62493:2015;EN IEC 61000-3-2:2019+A1:2021;EN 61000-3-	PF≥0.9	99.7*51.6*34.0mm
					UK							
IP44	54W (54G Version)				US	100-240VAC	36V-42V	1.5A max	ETL,FCC,DOE,CEC	ETL UL1310,FCC Part 15	PF about0.4-0.5	95.0*51.0*34.1mm
IP44	54W (54GH Version)				EU	200-240VAC	36V-42V	1.5A max	CE(EMC/LVD)	EN 61347-1:2015/A1:2021; EN 61347-2-13:2014+A1:2017; EN IEC55015:2019/+A11:2020;	PF≥0.9	99.7*51.6*34.0mm
					UK							
IP65/IP67	36W (36GA Version)				US Desktop	100-240VAC	5V-42V	5A max	ETL,FCC	UL1310,FCC Part 15	PF about0.4-0.5	98.3* 51.9 * 36.0mm
IP65/IP67	72W (72A version)				US Desktop	100-240VAC	12V-36V	5A max	ETL,FCC	UL1310,FCC Part 15	PF about0.4-0.5	116.7* 57.0 * 36.0mm
IP65/IP67	72W (72AH version)				EU Desktop	200-240VAC	12V-36V	5A max	GS,CE,LVD	EN 61347-1:2015/A1:2021; EN 61347-2-13:2014+A1:2017; EN IEC60598-1:2021+A11:2022; EN IEC55015:2019/+A11:2020;	PF≥0.9	116.7* 57.0 * 36.0mm
					UK Desktop							