
	Winstars Product Specifications		Version	A0
			Page	1/1
	Model	WS-UMD07	Date	3th-Nov-2021
	Name	Ergonomic laptop stand with type c dock	Writer	Nick
Picture		Features 特点		
		1: Ergonomic, Foldable Adjustable design. 2: widely compatible with all 10 to 17 inches laptops. 3: Lan support 10/100/1000Mbps. 4: SD/Mirco SD 3.0 version, can be read at the same time. 5: HDMI 2.0 dual 4K 60Hz outputs. 6: USB Power Deliver 85W. 7: USB3.0*2, data transmission up to 5Gpbs. 8. Support OS Windows 7 / 8 / 10; Max OSX 10.11; Linux or the latest version.		
Title 标题		Package Content 标配		
Ergonomic laptop stand with type c dock		Ergonomic laptop stand with type c dock User Manual C to C cable(E-Mark Chip)		
Description 介绍		System Requirement 系统配置		
laptop stand's Z-type design is good for adjusting an ideal height for typing, watching and sitting properly while supporting your back and neck with a comfortable posture. It will relieve the stiffness of your back and neck. It also can connect to your MacBook or other USB-C devices with the multiport USB-C hub featuring an Ethernet port, a USB C charging port with power delivery, two 4K/60Hz HDMI port, a SD card reader, a TF card reader, 2 USB 3.0 Ports, allowing you to connect a keyboard, USB driver, external Disk to your USB-C devices. This USB C hub applies to all laptops with type-c port.		Operating System support Windows 7, 8, 10 Mac OS X 10.11 and latest Chrome OS Linux		
Specification 规格				
Hardware 硬件		Functions 功能		
Ports	Type C to HDMI*2+USB C*2+USB3.0*2+SD+Mirco SD+RJ45	Working Standards	1: USB3.0 A/Fx2, data transmission up to 5Gpbs 2: HDMI support 4K@60Hz(HDMI2.0) 3: widely compatible with all 10 to 17 inches laptop 4: Lan support 10/100/1000Mbps 5: SD/Mirco SD 3.0 version, data transmission up to 5Gpbs, can be read at the same time 6: Type C PD*1 (can be support 85W) 7: Two-Level Adjustable 8: Heat Dissipation Design 9: Raise the laptop screen to improve your posture while working	
Button	NIL			
LED	NIL			
Chipset	VMM5200+VL817+VL170+VL103R+AX88179A+GL3224			
SDRAM	NIL			
Power Supply	Bus power			
Power Plug	NIL			
Power Consumption	<200mA		Max.charging current(A)	4.3A
Rated Voltage/ frequency /current	20V			
Dimensions 尺寸		Certification 证书		
Unit Dimensions	205x240x65MM (L x W x H)	CE-EMC	Available	
Weight	900g	CE-RTTE	Available	
Housing Material	Aluminium alloy + ABS plastic	CE-LVD	Available	
Shell color	Apple Gray	FCC DOC	Available	
Package	By design	FCC ID	Available	
Environmental 环境		ROHS	Available	
Operating Temperature	0°C~40°C	Reach	Available	
Storage Temperature	-10~70°C	3C	Available	
Relative Humidity(Operational)	10%~90%, noncondensing	Others 其他		
Relative Humidity(Storage)	10%~90%, noncondensing	Method	See Manual	
Drop test (1 Meters)	3 st	Performance	See Test Report	
Cycle work (hours)	24H	Reliability	See Test Report	

