

2.0MP 18X Economic HD Network Block Zoom Camera	
HD-3206AL	
1/2.8" 2.0M Pixels Progressive Scan CMOS	
PAL/NTSC	
5.3mm -96.3mm,18X	
F1.6~F3.5	
64.1° (Wide) / 3.6° (Tele)	
1000-1500mm(Wide-Tele)	
Approx 3s(Optical Wide-Tele)	
1920*1080, 1-25(30)fps; 1280*720, 1-25(30)fps	
640*480, 1-25(30)fps; 480*360 1-25(30)fps; 352*288, 1-25(30)fps; 176*144, 1-25(30)fps	
1280*960, 1280*720, Close	1920*1080, 1280*720, Close
Color: 0.05Lux@(F1.6 , AGC ON) B/W: 0.01Lux@(0F1.6 , AGC ON)	
Digital WDR, ≥62.5dB	
≥50dB (AGC OFF)	
Auto / Manual	
Auto/Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp	
DNR,3DNR	
Auto/Manual/shutter mode (shutter range variable)	
1/2 - 1/20,000s	
Day / Night / External control (IR Cut Filter)	
254	
4 Patrol、4 Pattern、Pan scan	
Click centering, Zoom by mouse dragging	
Dual streams	
CBR/VBR, bitrate: 32Kbps~10Mbps variable	
H.264 Main Profile /M-JPEG	
G711, PCM	
Support zoom、camera name、time display, OSD position can be adjusted	
Main stream Up to 3,Main stream Up to 6	
Android、IOS	
TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, P2P	
Support	
4 privacy masks programmable	
Onvif 2.4	
10/100M Base-TX Ethernet, RJ45 Connector	
Up to 32GB(Optional)	Up to 64GB(Optional)
Unsupport	1Vp-p Composite Output (75Ω/BNC)
1/1(Optional)	
1 input (Linear level, Resistance: 1000 Ohm); 1 output (Linear level, Resistance: 600 Ohm);	
Support wifi/4G USB module(Optional)	
12VDC@0.25A	
88x55x50mm	
-30°C ~60°C, Humidity≤90%RH(Unsupport-condensing)	