

Model	SP05C SERIES For Euro, AU Type	
Electric rated	10A, 250Vac, 3680Watts	
Number o outlets	5	
Grounded outlet	5	
Socket types	German / French / Italy / Australia	
Surge Energy Joules Rating	630Joules / (775Joules for USA version)	
Cable	100% copper H05VV-F 3G x 1.0mm ² x 1.0meter, 3G, with grounded	
Surge Lines protected	3line(L-N, L-G, N-G)	
Surge light indicator	Yes	
Ground light indicator	Yes	
Circuit Breaker in Amp	10A, individual circuit breaker	
Response time	<1 nanosecond	
Master Switch	push-button 2pole	
EMI/RFI filtering	100Khz-20Mhz	
Attenuation	Up to 30dB	
Maximum spike current	19500Amps	
Maximum voltage in volt	500V	
Maximum Spike Voltage	6000V	
Wall mountable	Yes	
USB charger	DC 5V 2.4A (2 Ports); DC 5V 3.1A (2 Ports) (Optional)	
type-C charger	1 port, 3 USB ports + 1 type-C port: DC 5V 5A 25W(Optional)	
Product color	Black, Grey, White	
Material	PC94V0 fire-proof, inflammable plastic	
Warranty	More than 3years under normal use	

Special Specification	UK Type	USA Type
Electric rated	13A, 250Vac, 3680Watts	15A, 125Vac
Cable	100% copper H05VV-F 3G x 1.0mm ² x 1.0meter, 3G, with grounded, BS plug with fuse	100% copper SJT16AWG 3G x1.0meter, 3G, with grounded, USA plug
Circuit Breaker in Amp	13A, individual circuit breaker	15A, individual circuit breaker