



## 4X/10X 2.0MP TVI Bullet WS-BT-HDT345



### Product Overview

- ※ Powerful compatibility, support ONVIF2.2
- ※ Support narrowband transmission, quality first and frame rate priority optional
- ※ Support H.264/MJPEG double compression, three bit stream, video output
- ※ Support P2P cloud monitoring
- ※ Support whole course 4X/10X focus, 2.8-12mm lens
- ※ Dual system backup, A-B scan, tour available
- ※ Support pan 0~220° auto cruise.
- ※ Total metal body construction, Support 6KV lightning protection, anti-surge function.

### Technical Specification

| Model No.              | WS-BT-HDT345                                                     |                |
|------------------------|------------------------------------------------------------------|----------------|
| Module                 | 323V                                                             | 321V           |
| Lens                   | 4X 2.8mm~12mm                                                    | 10X 5.1mm~51mm |
| Sensor                 | 1/3" Progressive scan CMOS                                       |                |
| Total pixel            | 2.0MP                                                            |                |
| Resolution             | HD:1080P/30fps /1080p/25fps                                      |                |
| Rotation               | Pan: 160°                                                        |                |
| Pan speed              | 0-30°/s                                                          |                |
| IR range               | 30M                                                              |                |
| IR control             | PWM                                                              |                |
| AB scan                | Support, 0-160 degree                                            |                |
| AB speed               | 1-9 grade selectable                                             |                |
| Preset                 | 220                                                              |                |
| Tour                   | 3 groups ( each group 16 preset、dwell time and speed selectable) |                |
| Calibration            | support                                                          |                |
| FOV                    | H: 106.6° (W) ~51.8° (T) V: 76.8° (W) ~38.8° (T)                 |                |
| BW                     | Auto                                                             |                |
| Focus                  | Auto/Manual                                                      |                |
| BLC                    | Adjust                                                           |                |
| Power                  | DC12V(2A)                                                        |                |
| Temperature            | Indoor: 0°~+40° Outdoor: -40° C ~+60° C                          |                |
| Video interface output | TVI                                                              |                |
| Communication mode     | RS485 (+/-) / coaxial cable                                      |                |
| Thunder Proof          | 6000V                                                            |                |
| Waterproof             | IP66                                                             |                |
| Package Size           | W265mm*D137mm*H130mm                                             |                |
| Weight                 | NW: 0.83KG/GW: 0.98KG                                            |                |

※※※Product specification are subject to change without notice※※※

[www.winsafecctv.com](http://www.winsafecctv.com)