

Product Paramenters

MYIXI DC Adapter Products specifications (NOT ALL)				
Universal input 100-240V~50/60Hz				
Input current 2.0A Max				
General outputs:				
5V6A	9V4A	13V3A	19V2A	29V2A
5V7A	9V4.5A	13V4A	19V2.1A	29.4V2A
5V8A	9V5A	13V5A	19V3A	30V1.5A
5.5V6A	9V6A	13.5V3A	19V3.42A	30V2A
5.5V8A	9V7A	13.5V4A	20V2A	33.6V1.8A
6V6A	9.5V4A	14V3A	20V2.5A	35V1.5A
6V7A	9.5V6A	15V3A	20V3A	35V1.8A
6V8A	10V4A	15V3.5A	21V3A	36V1.5A
7.5V5A	10V5A	15V4A	22V2A	36V1.8A
7.5V6A	12V3A	16V3A	22V2.5A	40V1A
8V4A	12V3.5A	16V4A	22V2.9A	40V1.5A
8V5A	12V4A	16.8V3A	24V2A	42V1A
8V6A	12V4.5A	16.8V4A	24V2.2A	42V1.5A
8V7A	12V4.8A	18V2A	24V2.5A	45V1A
8.4V4A	12V5A	18V2.2A	24V2.7A	46.2V1A
8.4V5A	12.6V3A	18V3A	25V2A	48V1A
8.4V6A	12.6V4A	18V3.5A	19V2.5A	48V1.2A
8.4V7A	12.6V4.5A	14V4A	25V2.2A	48V1.3A