

Product description:

A pyramid fast suture of silicone waterproof cover is designed for waterproofing roof design, particularly suitable for all kinds of round tubular seepage control requirements, but before installation must according to the tube diameter cutting to the appropriate size.

Product technical parameters

Materials: Silicone or EPDM
Color: Black / Red / Gray
Rim: Aluminum
Thickness: 1.5-2.0mm
Warranty: 25 Year

Base Size	Apply pipe size		
mm	mm	or	inch
100x100mm	0-35mm	or	0-1 $\frac{1}{2}$ "
200x200mm	50-100mm	or	2-4"
275x275mm	95-197mm	or	3 $\frac{3}{4}$ " - 7 $\frac{3}{4}$ "
310x310mm	100-200mm	or	4-8"

Product advantage

- Convenient installation
- Suitable for any shape of the roof
- Can withstand the extreme temperature -50° C to 150° C
- More effective waterproof measures
- Do not produce wrinkles, no leakage hidden trouble
- Product appearance concise
- Twenty-five Year warranty


25 YEAR
WARRANTY

Installation Instructions:



1

- Trim the cone to suit pipe size using sharp tin snips.




2

- Slide Dektite flashing down over pipe. Lubricating the pipe with water allows the pipe to slide snugly into position.




3

- Apply a neutral-cure silicone sealant by turning back the flexible flange.




4

- Press base to the roof profile by hand, smooth out any awkward creases. Don't fully extend to allow for vibration.



5

- Fasten using self-drilling washers. Fit fasteners progressively outward in opposing pairs to avoid gaps.



6

- Finished

