

POS Printer HCC-TL21

Feature

- 1", 2" label size available
- Automatic label peeling
- Compatible with CPCL, ESC/POS, TSC command set

Specification

Printing Method	Thermal Line
Resolution	8 dots/mm (203dpi) , 384 dots/line
Printing Speed	Max 127mm/s, General 101mm/s
Effective Printing Width	Max 56mm
Paper Width	57mm±0.5mm
Printing Head Temp Detection	Yes
Paper-out Sensor	Yes
Self-defined character	Yes
Graph Printing	Diagram, downloaded bitmap supported
Print Font	Code page; ANK: 9 x17 / 12 x24; Chinese: 24 x 24
Barcode	UPC-A; UPC-E; EAN-13; EAN-8; CODE39; CODE93; CODABAR ; ITF25; CODE128
Interface	USB+Ethernet
Other Functions	Paper-out alarm, Black-mark detection, Over-heat protection, Buzzer
Cash Drawer	DC12V/24V , 1A , 6pin RJ-11 socket
Power supply	DC12V±10%, 2A
Paper Type	Normal thermal paper: Max 57×Ø80mm, Min 57×Ø25mm
Paper Thickness	0.06mm ~ 0.14mm
Paper Supply Method	Drop-in easy paper loading
Paper Cutting Method	Manual, Auto-peel (label paper)
Operating Temp/Humidity	0~50°C/10~80%
Storage Temp/Humidity	-20~60°C/10~90%
TPH	60km

Picture

