

LED LIGHTING

MINER'S LAMP THE LITHIUM BATTERY MINER'S LAMP SERIES


PRODUCT APPEARANCE




(Note: the lithium battery miner's lamp series, the same parameters, the appearance of different styles.)

PRODUCT PARAMETERS

Model	KL4LM Mining Lamp
Rated voltage	3.7V
Rated capacity	4Ah
Lighting time	> 20H
Charging time	6-8H
Illumination(Start) (11H After)	≥4500lux ≥3000lux
Luminous flux	130LM
Unit Packing Size	13*12*13cm
Carton packing size	50*28*58cm
Packing quantity	40pcs/ctn
Net weight	500g
Battery life	≥500 times charging cycle
Working temperature	-10 ~ 45 °C



SPECIFICATION SIZE



PRODUCT FEATURES

1. Using LED light source, high luminous efficiency, long service life, in the period of the service life of the miner's lamp don't have to replacing the power supply.
2. Using electronic manganese acid lithium battery, battery is fully sealed structure, does not leak liquid, miner's lamp battery without having to use period maintenance, safety performance is best
3. Used the reusable miner's protector device, charging protection and short circuit protection function, can quickly cut off the circuit when a miner's lamp is a short circuit, to avoid an accident.

LED LIGHTING

MINER'S LAMP THE LITHIUM BATTERY MINER'S LAMP SERIES

PRODUCT APPEARANCE



PRODUCT PARAMETERS

Model	RD400 Mining Lamp
Rated voltage	3.7V
Rated capacity	4Ah
Lighting time	> 20H
Charging time	6-8H
Illumination(Start) (11H After)	≥4500lux ≥3000lux
Luminous flux	130LM
Unit Packing Size	13*12*13cm
Carton packing size	50*28*58cm
Packing quantity	40pcs/ctn
Net weight	500g
Battery life	≥800 times charging cycle
Working temperature	-10 ~ 45 °C

PRODUCT APPEARANCE



PRODUCT PARAMETERS

Model	RD500 Mining Lamp
Rated voltage	3.7V
Rated capacity	5Ah
Lighting time	> 24H
Charging time	6-8H
Illumination(Start) (11H After)	≥9000lux ≥5000lux
Luminous flux	130LM
Unit Packing Size	13*12*13cm
Carton packing size	50*28*58cm
Packing quantity	40pcs/ctn
Net weight	500g
Battery life	≥800 times charging cycle
Working temperature	-10 ~ 45 °C