





深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co.,Limited

Add: Building 26,Dingfeng Science Industrial Park,No 2 Xingye 1st Road,Fenghuang village,Fuyong Town baoan district, Shenzhen, China
Contact Person: [Nancy Wu](#) Mob/WhatsApp: [+86 15920053974](#) Wechat: [Sophia-xhy](#)
Email:Nancy@szxgled.com
Web: www.xgled.com <https://szxgled.en.alibaba.com>

P6 Outdoor LED Display Parameter

LED Module		
	pixel pitch	6mm
	module size	192*192mm
	module resolution	32*32dots
	LED	SMD3535
	Scan	1/8scan
	Application	Outdoor
	Weight	0.35KG
	Chip type	Epistar

LED Cabinet		
	Cabinet Size	960mm (W) *960mm (H)
	Cabinet resolution	160*160dots
	module quantity	5*5pcs
	LED driver brand	5V 60A 220V
	Material	Sealed waterproof iron case
	Receiving card	1pcs

LED Screen				
	Pixel	27777dots/m²	Continuous Working Hours	>72 hours
	Ave power consumption	450W/m²	Using Life	100,000 hours
	Max power consumption	900W/m²	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥6m	Scatter OOC Point	<0.01%
	Brightness(cd/m²)	≥5500cd	Continuous OOC Point	None
	Refresh Rate	960 HZ	IP Grade	IP65
	LED Drive mode	Constant Current	Working Temperature	-35C-----+60C
	Display color	17M——69G	Working Humidity	10---90%



深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co., Limited

4.Regular packing:



5.Certifications: CE ROS FCC CCC

