

| Model | SP04A SERIES For Euro Type |
|----------------------------|--|
| Electric rated | 10A, 250Vac, 3680Watts |
| Number o outlets | 4 |
| Grounded outlet | 4 |
| Socket types | German / French / Italy |
| Surge Energy Joules Rating | 210Joules |
| Cable | 100% copper H05VV-F 3G x 0.75mm ² x 1.5meter, 3G, with grounded |
| Surge Lines protected | 1line(L-N) |
| Surge light indicator | Yes |
| Response time | <1 nanosecond |
| Switch | push-button 2pole |
| Maximum spike current | 6500Amps |
| Maximum voltage in volt | 500V |
| Maximum Spike Voltage | 6000V |
| Wall mountable | Yes |
| Tel/Fax/Modem protection | 1 in 1 out RJ11 / RJ45 protection connector (Optional) |
| TV protectoin(coaxial) | 1 in 1 out Coaxial protection connector (Optional) |
| Product color | Black, Grey, White |
| Material | PC94V0 fire-proof, inflammable plastic |
| Warranty | More than 3years under normal use |

| Special Specification | Australia Type |
|------------------------------|---|
| Electric rated | 10A, 250Vac |
| Cable | 100% copper H05VV-F 3G x 1.0mm ² x 1.5meter, 3G, with grounded, Australia plug |