

型号/Model
TOUC29

GaN 45W
氮化镓(GaN)



智能引擎

卓越识别

精准判断

安全高效

工作环境 (Working Environment)

工作温度(Operating Environment): $-10^{\circ}\text{C} \sim 30^{\circ}\text{C}$
 存储温度(Operating Temperature): $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
 湿度(Humidity): $5\% \sim 95\%\text{RH}$

技术参数 (Spec)

输出电压(Output Voltage): 单口: USB C: 5V 3A/9V 3A/12V 3A/15V 3A/20V 2.25A

PPS1: 3.3 ~ 11V 3A PPS2: 3.3 ~ 16V 2.8A

USB A: 5V 3A/9V 3A/12V 3A/20V 1.8A

双口同时工作: USB A: 5V 3A/9V 2A/12V 1.5A

USB C: 5V 3A/9V 3A/12V 2.5A/15V 2A/20V 1.5A

PPS1: 3.3 ~ 11V 3A PPS2: 3.3 ~ 16V 2A

兼容协议(Compatibility Protocols): PD3.0/PD2.0/QC3.0/QC2.0/AFC/FCP/DCP/App2.4A

额定输入(Rated Input): 100~240V AC 50/60Hz 1.5A

能将等级(Efficiency Level): VI

安全标准(Safety Standard): IEC/UL/EN62368(GB4943)

电磁兼容(EMC): EN55032 EN55024 EN55015 EN61000(GB9254 GB17625 GB13837)Part15 subpart B

认证(Certificates): ETL FCC CE UKCA SAA

尺寸大小(Size): 57.3mm*29mm*57.6mm

