



# Shenzhen Triwin Technology Co., Ltd

Add: 3F, Zhongguang Industrial Zone No. 371 (3702)  
Xixiang Section, Bao'an District, Shenzhen, China  
Tel: +86 755 2270 1168 M: +86 181 2686 4312  
Email: kate.peng@triwin-gd.com URL: www.triwin-gd.com

## Smartphone Backup Disk



## Smartphone Backup



|                                     |                                                            |
|-------------------------------------|------------------------------------------------------------|
| Model No.                           | SB                                                         |
| Net Weight                          | ~295g                                                      |
| Dimension                           | 130*85*23MM(Approx.) & 18°W                                |
| Color                               | Black/White (Blue is optional)                             |
| Shell                               | Aluminum and Plastic                                       |
| Storage capacity                    | 2.0" 500GB/1TB/2TB HDD 5400RPM (2.5" Data SSD is optional) |
| Built-in battery                    | 2.7V 5000mAh/18.5Ah (Polymer Lithium)                      |
| Supporting OS                       | iOS, Android (Please refer to the user manual)             |
| Sockets                             | USB A 3.0*1, SD*1, Micro USB 3.0*1                         |
| Buttons                             | Power*1                                                    |
| LED Light for working               | Blue*1                                                     |
| LED Light for battery               | White*3                                                    |
| Accessories                         | 30cm Data-Charging Cable*1                                 |
| Sequential Read Speed(Min to Max.)  | 80-60MB/s for HDD version; 150MB-300MB/s for SSD version   |
| Sequential Write Speed(Min to Max.) | 80-60MB/s for HDD version; 150MB-300MB/s for SSD version   |
| Random Read Speed                   | 80-60MB/s for HDD version; 150MB-300MB/s for SSD version   |
| Working Voltage                     | Input: 5V 2A; Output: 5V & 5A                              |
| Working Current                     | Less than 400mA                                            |
| MTBF                                | 1,500,000hours                                             |
| Working Environment                 | 2 to 40°C Temperature @ 20-60% Humidity                    |
| Storage Environment                 | -10 to 55°C Temperature @ 20-60% Humidity                  |
| Warranty                            | 1 year                                                     |
| Certificate                         | CE, RoHS, Reach (FCC is optional)                          |
| HS Code                             | 8471701100                                                 |