



SPECIFICATIONS :

Voltage Rating: 250V AC / DC
 Current Rating: 3A AC / DC
 Withstanding Voltage: 1500V AC/minute
 Temperature Range: -25°C~+85°C
 Insulation Resistance: 500MΩ Min.
 Contact Resistance: 15mΩ Max.
 After environmental testing: 20mΩ Max.
 Wire Range: AWG#22~30.
 *Suitable LDZY C2505TF series Terminal
 *Mates with LDZY A2501WR(V)B series Wafer
 Material: Nylon66, UL94V-0

A2501 H B - NP - N0 NA 1
 ① ②③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: H-Housing
- ③ Colloid Feature: Blank-Common, B-With hook
- ④ Circuit No.:02~16PIN
- ⑤ Material: N0-PA66, UL94V-0
- ⑥ Color: BK-Black, BN-Brown, BL-Blue, RE-Red, GN-Green, WH/WT-White, YW-Yellow,
- ⑦ Other:1-无LOGO

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	2.50	5.90	14	32.50	35.90
03	5.00	8.40	15	35.00	38.40
04	7.50	10.90	16	37.50	40.90
05	10.00	13.40	17	40.00	43.40
06	12.50	15.90	18	42.50	45.90
07	15.00	18.40	19	45.00	48.40
08	17.50	20.90	20	47.50	50.90
09	20.00	23.40	21	50.00	53.40
10	22.50	25.90	22	52.50	55.90
11	25.00	28.40	23	55.00	58.40
12	27.50	30.90	24	57.50	60.90
13	30.00	33.40	25	60.00	63.40

						一般公差 GENERAL TOLERANCE .X ±0.30 .XX ±0.20 .XXX ±0.10				 东莞市蓝雁电子有限公司 DongGuan LDZY Electronics CO.,LTD.				料号 PART NO A2501HB-NP-N0XX1					
						核准 APPD				审核 CHK		绘图 DR		日期 DATA		品名 TITLE 2.50mm Pitch Wire to Board Connector			
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION			审核 CHK	核准 APPD	角法 	PROJECT Rodney	兰雄	潘昌文	2021/03/28	单位 UNIT mm	比例 SCALE 1/1	图号 NUMBER LDZY-8801	版次 REV A			