

4G LTE 4K Dash Cam

Model: iSV-G4K(4G&4K)



Main Features:

- * 4G / 4K Cloud Dash Cam / Dual Channels
- * H.265 / 4G Module + SONY IMX415 Sensor
- * 4K + 1080P, 30Fps / WDR / Super Night Vision
- * Remote Live Video / GPS Tracking / DVR
- * Remote Playback / Support App & PC Platform
- * Support SOS Alarm / Parking Monitoring
- * Support Vibration Alarm / Anti-theft Alarm
- * Support Geofence Alarm / Over-speed Alarm

-
- ① 4G & WiFi Connection, 4K (3840x2160) Resolution
 - ② 4G Module, ARM A7 1.0GHz(4 Core) IPU, Linux4.19 System
 - ③ Sony IMX415 Sensor, 8.0Mega Pixels
 - ④ H.265, 4K+1080P Dual Channel, 30Fps, MP4
 - ⑤ WDR, Super Night Vision, with G-Sensor
 - ⑥ Maximum Support 512GB SD Card
 - ⑦ 4G+WiFi, Live Video Remotely by App or PC Platform
 - ⑧ Ultra wide 158° View Angle captures more of the road around you
 - ⑨ Enjoy Free GPS Tracking Services
 - ⑩ Support Parking Monitor, Support Time-Lapse Record
 - ⑪ Support Low Battery Protection
 - ⑫ SOS Alarm, Anti-Theft Alarm, Geofence Alarm, Over-speed Alarm

Specification:

Model		iSV-G4K
Hardware	4G Module	Quectel EC200D (Europe Version)
	IPU	ARM A7 1.0GHz(4 Core)
	Sensor	Sony IMX415 Sensor / 8.0Mega Pixels, WDR, Super Night Vision
	OS	Linux4.19 System
	RAM	LPDDR4 1GB RAM
	IPS Screen Size	No
Network / Data	LTE UE-Category	Cat.4
	4G / LTE-FDD	B1/B3/B5/B7/B8/B20/B28
	4G / LTE-TDD	B38/B40/B41
	WCDMA(3G)	B1/B5/B8
	Data Service	LTE, WCDMA, HSDPA, HSUPA
	GPS Location	GPS, A-GPS, BeiDou
	Wi-Fi	2.4G/5G, WLAN
Main Functions	DVR	H.265, 4K(Front)+1080P(Rear) with 30fps, Loop-Recording
	WDR	Support

	Super Night Vision	Support
	GPS Tracking	Support, App & PC Platform
	G-Sensor	Support
	Remote Monitoring	App & PC Platform, Remote Video and Remote Picture
	Playback	Support App playback with WiFi and Remotely
	Live Streaming Video	Front-Car/Rear-Car Live Streaming Video Via APP or PC Platform
	Cameras	Front Camera: UHD 4K, Adjustable viewing angle 155°
		Rear Camera: 1080P, Viewing angle 145°
	Micro SD Card	Support Max 512GB
	Time-Lapse Record	Support, 12H / 24H / 48H Optional
	Low Battery Protection	Support
	Parking Monitoring	Support
	SOS Alarm	Support
	Anti-Theft Alarm	Support
	Geofence Alarm	Support
	Over-speed Alarm	Support
Others	Operating Temperature	-20℃~70℃
	Operating Humidity	0~90%, Non-Condensed
	Dimension(L*W*H)	109(L)*52 (W)*33(H)mm