

Technical Specifications

Processor	IOTC 0370 CHIP
Interface	RS-232 (9.6~115.2Kbps)
	USB 1.1 (HID-KBW, HID-POS)
Image Sensor	752×480 CMOS
Symbologies	2D: PDF417, Data Matrix, QR Code 1D: EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar (RSS-Expand, RSS-Limited, RSS-14), Code 39, Code 11, MSI-Plessey, Plessey
Scan Mode	Sense mode
Resolution	10 mil
Light Source	White LED
Scan Window	38.3mm*60.4mm
PCS	≥30%
FOV	Diagonal: 85°, Horizontal: 63.7°, Vertical: 70°
Ambient Light	0 ~ 100,000 LUX
Power Consumption	1.75W (max.)
Power Adapter	Output: DC5V, 0.5A, Input: AC100~240V, 50~60Hz
Notification	Beep
Dimensions	82 mm(L) X 7 2mm (W) X 52mm(H)
Weight	300g
Operating Temperature	-10℃ to + 50℃
Storage Temperature	-20℃ to + 60℃
Humidity	5% - 95% (non-condensing)
Certification	FCC Part15 Class B, CE EMC Class B