

Item	Model / Picture	Discription
	GY3018GBTG	Light power: 120w (80-120W), Input voltage: AC220V 50/60HZ, PF>0.95, Light size: 299x186x180mm, Material: Die-casting aluminum, NW: 6.2kg, IP66, LED: Cree 2020, LPW: 97.77lm/w, Beam angle: 90 degrees, CCT: 3000-6500K, Ra>70, Explosion proof Level: Exdb II BT6Gb;Extb III CT80°C Db
	GY3828GBTG	Light power: 200w (80-200W), Input voltage: AC220V 50/60HZ, PF>0.95, Light size: 376x277x158mm, Material: Die-casting aluminum, NW: 9.8kg, IP66, LED: Cree 2020, LPW: 120lm/w, Beam angle: 90 degrees, CCT: 3000-6500K, Ra>70, Explosion proof Level: Ex db II B T6/T5/T4 Gb;Ex tb IIIC T80°C/T95°C/T130°C Db
	GY4732GBTG	Light power: 280w (150-280W), Input voltage: AC220V 50/60HZ, PF>0.95, Light size: 474x315x1988mm, Material: Die-casting aluminum, NW: 12.5kg, IP66, LED: Cree 2020, LPW: 112lm/w, Beam angle: 90 degrees, CCT: 3000-6500K, Ra>70, Explosion proof Level:Ex db eb mb ITC T5/T6 Gb Ex tb IIIC T95/80°C Db
	GY210GB	Ligh power: 60w (10-60w), LED: 3030-60 pcs, Light size: D211x158mm, NW: 2.6kg, Beam angle: 110 degrees, Input voltage: AC220V 50/60HZ, IP66, LPW: 120lm/w, PF>0.95, CCT: 3000-6500K, Ra>70, Start time: <0.2s, Explsion proof Level: Ex nR II C T6 Gc; Ex tb IIIC T80°C Db
	GY250GB	Ligh power: 80w (60-80w), LED: 3030-80 pcs, Light size: D254x181mm, NW: 3.4kg, Beam angle: 115 degrees, Input voltage: AC220V 50/60HZ, IP66, LPW: 120lm/w, PF>0.95, CCT: 3000-6500K, Ra>70, Start time: <0.2s, Explsion proof Level: Ex nR II C T6 Gc; Ex tb IIIC T80°C Db
	GY280GB	Ligh power: 120w (80-120w), LED: 3030-120 pcs, Light size: D276x177mm, NW: 4.2kg, Beam angle: 112 degrees, Input voltage: AC220V 50/60HZ, IP66, LPW: 120lm/w, PF>0.95, CCT: 3000-6500K, Ra>70, Start time: <0.2s, Explsion proof Level: Ex nR II C T6 Gc; Ex tb III C T80°C Db
	GY330GB-50W	Light power: 50w, Input voltage: AC100-277V 50/60Hz, IP66, Ra>70, PF>0.9, CCT: 3000/4000/5000/5700K, LPW: 125lm/w, Light size: 330x280x244.5mm, NW: 7kg, House material: Die-casting aluminum, House color: Yellow, Life time: 50000h, Beam angle: 80 degrees, Explosion proof level: Ex db IIB T4 Gb / Ex db IIB T6 Gb,
	GY330GB-60W	Light power: 60w, Input voltage: AC100-277V 50/60Hz, IP66, Ra>70, PF>0.9, CCT: 3000/4000/5000/5700K, LPW: 125lm/w, Light size: 330x280x244.5mm, NW: 7kg, House material: Die-casting aluminum, House color: Yellow, Life time: 50000h, Beam angle: 80 degrees, Explosion proof level: Ex db IIB T4 Gb / Ex db IIB T6 Gb,
	GY330GB-70W	Light power: 70w, Input voltage: AC100-277V 50/60Hz, IP66, Ra>70, PF>0.9, CCT: 3000/4000/5000/5700K, LPW: 125lm/w, Light size: 330x280x244.5mm, NW: 7kg, House material: Die-casting aluminum, House color: Yellow, Life time: 50000h, Beam angle: 80 degrees, Explosion proof level: Ex db IIB T4 Gb / Ex db IIB T6 Gb,
	GY402GB-120W-140W	Light power: 120w or 140w, Input voltage: AC100-277V 50/60Hz, IP54, Ra>70, PF>0.97, CCT: 3000/4000/5000/5700K, LPW: 100lm/w, Light size: D402x326mm, NW: 15.9kg, House material: Die-casting aluminum, House color: Yellow, Life time: 50000h, Beam angle: 60 degrees, Explosion proof level: Ex d IIC T5 Gb

	GY402GB-150W-160W	Light power: 150w or 160w, Input voltage: AC100-277V 50/60Hz, IP54, Ra>70, PF>0.97, CCT: 3000/4000/5000/5700K, LPW: 100lm/w, Light size: D402x326mm, NW: 15.9kg, House material: Die-casting aluminum, House color: Yellow, Life time: 50000h, Beam angle: 60 degrees, Explosion proof level: Ex d IIC T5 Gb
	GY402GB-170W-200W	Light power: 170w or 200w, Input voltage: AC100-277V 50/60Hz, IP54, Ra>70, PF>0.97, CCT: 3000/4000/5000/5700K, LPW: 100lm/w, Light size: D402x326mm, NW: 15.9kg, House material: Die-casting aluminum, House color: Yellow, Life time: 50000h, Beam angle: 60 degrees, Explosion proof level: Ex d IIC T5 Gb