


CN1	
NO.	Name
1	VSS
2	VDD
3	VLCD
4	RS
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LED(+)
16	LED(-)

Interface: 68800

**SPECIFICATIONS:**

- 1.DISPLAY TYPE:STN/YELLOW-GREEN
- 2.VIEWING DIRECTION:6:00 O'CLOCK
- 3.POLARIZER MODE:TRANSPARENT/POSITIVE
- 4.DRIVE METHOD:1/16 DUTY,1/5 BIAS
- 5.OPERATING TEMP:-20°C---+70°C
- 6.STORAGE TEMP:-30°C---+80°C
- 7.WORKING VOLTAGE:VDD-VSS=+5.0VDC
- 8.BACKLIGHT:YELLOW-GREEN;LED(+)-LED(-)=+5.0VDC
- 9.ALL UNMARKED TOLERANCES:±0.15mm/±0.5°

**深圳市佳显电子技术有限公司**  
 Shenzhen Goodview Electronic Technology Co.,Ltd



绘图: 李建清	绘图编号: LCM-SJXD4002ADYSYMN	单位: mm
审核: 李建清	客户编号:	日期: 2024-01-02
批准:	图纸版号: V1	页数: 1/1
李建清	20240102	
Modified by	Date	
First issue		
Modify the content		
Version Mark		
Content		
Modify the content		
Version Mark		