


M12 C code male straight plastic assembly connector, unshielded/M12, C型公头直头塑胶装配式连接器, 不带屏蔽


Illustration/尺寸Product photo/产品图



Part number/产品料号

Pins/针数	Code/型	Part number/产品料号	
		PG7 thread/PG7螺纹	PG9 thread/PG9螺纹
2pins/2针	C code/C型	12ZU94-PG7	12ZU94-PG9
3pins/3针	C code/C型	12ZU96-PG7	12ZU96-PG9
4pins/4针	C code/C型	12ZU97-PG7	12ZU97-PG9
5pins/5针	C code/C型	12ZU99-PG7	12ZU99-PG9
6pins/6针	C code/C型	12ZU101-PG7	12ZU101-PG9

Pin assignment front view/针位分布前视图



General data/常规数据

Pin Numbers/针数	2pins/2针	3pins/3针	4pins/4针	5pins/5针	6pins/6针
Rated voltage/额定电压	250V			60V	30V
Rated current(40°C)/额定电流	4A				2A
Standards/标准	IEC 61076-2-101				
Termination/焊接方式	solder/焊接				
Degree of protection/防护等级	IP67, IP68, IP69K				
Wire gauge(mm²)/线规(平方数)	0.14mm²-0.75mm²				
Wire gauge(AWG)/线号(平方数)	26AWG-18AWG				
Mechanical operation/插拔次数	>100 mating cycles/大于100次				
Ambient temperature (operation)/操作温度	-25°C~+85°C				
Contact resistance/接触电阻	≤5mΩ				
Insulation resistance/绝缘电阻	≥100MΩ				
Connector body/胶芯	TPU				
Pins/端子	Brass with gold plated/黄铜镀金				
Screw/螺丝	Brass with nickel plated/黄铜镀镍				
Environmental compliance/环境符合标准	RoHs, Reach				