




深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co., Limited

Add: Building 26, Dingfeng Science Industrial Park, No 2 Xingye 1st Road, Fenghuang village, Fuyong Town baoan district, Shenzhen, China
Contact Person: [Nancy Wu](#) Mob/WhatsApp: [+86 15920053974](#) Wechat: [Sophia-xhy](#)
Email: Nancy@szxgled.com
Web: www.xgled.com <https://szxgled.en.alibaba.com>

P4 Outdoor LED Display Parameter

LED Module		
	pixel pitch	4mm
	module size	256*128mm
	module resolution	64*32dots
	LED	SMD2525/SMD1921
	Scan	1/8scan
	Application	Outdoor
	Weight	0.32KG
	Chip type	Epistar

LED Cabinet		
	Cabinet Size	1024mm (W) *1024mm (H)
	Cabinet resolution	256*256dots
	module quantity	4*5pcs
	LED driver brand	5V 60A 220V
	Material	Sealed waterproof iron case
	Receiving card	2pcs

LED Screen				
	Pixel	62500dots/m ²	Continuous Working Hours	>72 hours
	Ave power consumption	600W/m ²	Using Life	100,000 hours
	Max power consumption	1500W/m ²	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥4m	Scatter OOC Point	<0.01%
	Brightness(cd/m ²)	≥4000cd	Continuous OOC Point	None
	Refresh Rate	960 HZ	IP Grade	IP65
	LED Drive mode	Constant Current	Working Temperature	-35C--- +60C
	Display color	17M——69G	Working Humidity	10---90%



深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co., Limited

4. Regular packing:



5. Certifications: CE ROS FCC CCC

