

2 SATA 16CH POE H.265+ NVR Series PNVR-8256



Features :

- Support 8CH 4K/16CH 5M/3M video access storage;
- Support VGA 1080P, HDMI 4K output;
- Big 1U Case,2 SATA(Up to 8TB);
- H.265+/H.265/H.264 image decoding ;
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Supports the Onvif protocol and can connect to third-party devices;
- Support GB28181 protocol to access third-party platforms (optional);
- Support cloud service, network penetration and alarm information push function;
Support remote access, with its own domain name service function (ARSP) ;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, IP search, alarm center, etc.;
- Support mobile phone monitoring (iOS, Android);
- Support multiple browser access (IE, Chrome, Firefox,Safari);
- Support more than 20 languages and break the boundaries of national borders;
- Perfect protection circuit, unique triple watchdog function;
- Supporting WEB, CMS, VMS, MYEYE platform, providing SDK Development;

Parameters :

| Item | Model | PNVR-8256 |
|------------|---------------|--|
| System | Processor | Hi3536 |
| | System | Embedded LINUX operating system |
| Video | Encode | 8*4K/16*5M/16*3M |
| | Playback | 2*4K/4*5M/8*3M |
| | Codec | H.265+/H.265/H.264 |
| Audio | Compression | G.711A |
| | Intercom | Support |
| Management | Record mode | Manual>Alarm>Motion detection>Timing |
| | Inquire mode | Inquire by Time/Calendar/Event/Channel |
| | Storage mode | HDD Storage, Network Storage |
| | Backup | Network, USB, SATA |
| Interface | HDMI output | 1*HDMI (MAX:4K) |
| | VGA output | 1*VGA (MAX:1080P) |
| | Ethernet port | 1*10/100/1000Mbps Ethernet port, RJ45 port |
| | POE Port | 16*POE Ports |
| | POE Power | 15.4W-30W |
| | Whole Power | 400W |
| | USB Port | 1*USB 2.0 port,2*USB 3.0 port |
| | HDD | 2*SATA interface (Up to 8TB) |
| General | Temperature | 0 °C - + 55 °C |
| | Humidity | 10% -90% RH |
| | Power supply | ATX(100-240V AC) |
| | Consumption | <10W (Without HDD) |
| | Weight | Around 3.0KG |
| | Dimension | 440mm(L)* 290mm(W)* 50mm(H) |

Interface :

