




RS5 SERIES
ROTARY SWITCHES UP TO 130mA 150VDC/AC
 Optional actuator and PCB terminal



- Load Rating: 130mA 150VDC/AC
- Contact Resistance: 25 mΩ Max (initial)
- Insulation Resistance: DC 500V 100MΩ Min.
- Dielectric Strength: 1000VAC 1 Minute
- Mechanical Life: 20000 cycles Min.
- Electrical Life: 15000 cycles Min.
- Operating Torque: 1kgf-cm (Max)
- Operating & Storage Temperature: 0 °C ~ + 60 °C
- Soldering spec: 255 °C ± 5 °C Within 3 sec
- Rotary Angle: 30°
- Cap/ Case/ Movement: PA
- Moving Contact: PBS+Ag
- Spring: SUS

How to order:

RS5	—	C	—	12	—	NS
		Cap Style	Combination			Timing
A		No.	Pole	Position	Stop	YS Shorting
B		11	1	2	Yes	NS Non-Shorting
C	 <small>(Aluminum Shaft)</small>	12	1	12	Yes	
		13	1	12	No	
		21	2	2	Yes	
		22	2	6	Yes	
		23	2	6	No	
		31	3	2	Yes	
		32	3	4	Yes	
		33	3	4	No	
		41	4	2	Yes	
		42	4	3	Yes	
		43	4	3	No	
		61	6	2	Yes	
		63	6	2	No	

