


Guangdong Magic Electronic Limited

(Product inspection report)

Product: Super smooth self-healing microcrystalline screen protector

Grade No.:

◆ Product Structure



- The second protective film 50 μ
- Use layer substrate 110 μ (Super smooth self-repair)
- AB glue 280 μ
- The first side release film 50 μ

◆ Product Data

(Item)	(Unit)	(Value)	(Test results)
High temperature test	℃	80	24 hours no degumming no deformation
Low temperature test	℃	-20	24 hours no degumming no deformation
Total Thickness	mm	0.4±0.02	Qualified
Adhesion(G/50MM)	g	1000 (To Glass)	Qualified
Gluewater deviate Test	----	PASS	Qualified
(500g) Rigidity Test	h	Self-healing	Qualified
(Rainbow stripes test)	International color light	Low rainbow	Qualified
Local diaphaneity Test	----	100/ 100	Qualified
Diaphaneity Test	----	92%	Qualified (not for printing area)

◆ Note

1. The product should be packed well and stored up in the cool dry environment,avoiding straight sunshine,freezing and high temperature.(when season transforms,goods storage cannot too be many)
2. Sticking surface should be clean,smooth,dry,no fat or other pollutant.
3. The above technologies are the average data obtained through multiple tests by the company using recognized and reliable methods.However,in order to ensure the correct selection and use of our products,please make a detailed understanding and trial based on the object,purpose and conditions of the intended use,or notify the company so that you can make further instructions and services.