

Product name	Direct Deal Cold Rolled HRB400 HRB500 Thread Deformed Carbon Steel Rebar Reinforcing Steel Rebar for Building Construction
Standard	ASTM, AISI, EN, DIN, JIS, GB
Grade	HRB400/HRB500/KSD3504 SD400/KSD3504 SD500/ASTM A615, GR40/ASTM GR60/BS4449 B500B/BS4449 B460 Etc.
Material	HRB335, HRB400, HRB500, JISG3112-2004 SD390; BS4449-1997 Gr.460B; BS4449:2005 B500B/B500C
Specifications	Diameter(6-50mm) 6mm,8mm,10mm,12mm,16mm,20mm,22mm,25mm,28mm,32mm, 40mm,50mm Or OEM Length:6m-12m as your required
Application	Rebar is widely used in building, bridge, road and other civil engineering construction.
Standard	GB:HRB400 HRB400E HRB500
	USA:ASTM A615 GR40,GR60
	UK: BS4449 GR460
Inspection Methods	Tensile testing

	(1) Tensile test method: GB/T228.1-2010, JISZ2201, JISZ2241, ASTM A370, 1497, BS18, etc;
	(2) Bending test method: often use standard test methods have GB/T232-88, YB/T5126-2003, JISZ2248, ASTM E290, ROCT14019, etc.