

Shenzhen G-World Technology Co., Ltd.

Portable Monitor Specifications

Product Name: 173-kick stand (Mould Type)

Product Model: A1M

File Number: A1M-173

Release Date: 2024-06-26

Release Review: Lai Tzu Ki

Shenzhen G-World Technology Co., Ltd.

Product Basic Information

Product Model	A1M
Brand LOGO	ARZOPA
Selling Model	A1M
Physical Picture (front and back)	 
Physical Dimension	394*243*9.3mm (length,Width and Thickness)
Bare Weight	920g
Structural Features	Stamping process, all-aluminum alloy shell, one-piece shell
Screen Size	17.3" LCD Panel
Panel Type	a-Si TFT-LCD , LCD module, WLED light source
Screen Ratio	16:9
Screen Level	A (A+)
Pixel Pitch (mm)	0.1989×0.1989 mm [127PPI]
Dot Pitch (mm)	0.0663×0.1989 mm (W×H)
Screen size (mm)	381.888×214.812 mm
Brightness	The measured peak brightness is: 319.01 cd/m2 The standard brightness of the display is: 300 cd/m2
Static Contrast	1000:1

Shenzhen G-World Technology Co., Ltd.

Color Gamut	Color gamut Color gamut area ratio Color gamut coverage (measured data)				
	色域（实测数据）	色域面积比		色域覆盖率	
		CIE 1931	CIE 1976	CIE 1931	CIE 1976
	sRGB	103.37%	102.21%	99.46%	98.62%
	DCI-P3	76.20%	81.39%	75.99%	80.84%
	Adobe RGB	76.63%	87.63%	76.19%	85.49%
Viewing Angle	89/89/89/89 (Typ.)(CR≥10)				
	60Hz				
	11/9 (Typ.)(Tr/Td) (ms)				
	1920x1080P （FHD）				
	1920x1080/60Hz				
	16.7M (8-bit)				
Built-in Speakers	Built-in dual speakers (1W speakers*2)				
	HDR 10				
	8W				
	≤1W				
	1				
	-20 ~ 60 °C				
Storage Temperature	0 ~ 50 °C				
	Matte				
	Edge light source				
Operating Temperature					
Surface Treatment					
Light Source Characteristics					

Shenzhen G-World Technology Co., Ltd.

Product Ports and Button Functions

Illustration	
Signal Input	TYPE-C,HDMI
Signal Interface	TYPE-C (USB 3.1) *2, (Support PD power supply and DP output) miniHDMI (2.0) *1, (Compatible with most HDMI devices)
Power Input	Support 5~20V adapter (support PD input, PD reverse power supply)
Indicator Color	Red/Blue (the red indicator light is on when there is no signal, and the blue indicator light is on when there is a normal signal)
Button	4 buttons (OSD, + -, Power(exit))
Menu	ARZOPA OSD
Safety Certification	CCC FCC CE PSE ROHS HDMI

Shenzhen G-World Technology Co., Ltd.

Product Accessories

Dual Type-C Data Cables	Type-C 3.1 full-featured data cable (1 meter) 
HDMI-to-miniHDMI Cable	HDMI 2.0 Full HD Cable (1 meter) 
USB-A to USB-C Power Cable	
Notice	The measured data comes from ARZOPA laboratory