

HUARI COMMUNICATION INT'L LIMITED



Rm.605-606, Runtian Commercial Mansion, No.19, Runtian St.,
Baogang Rd., Haizhu, GZ, Guangdong.510240,China

Tel:86-20 6239 3483 Fax:86-20 6239 3488

Email: export@huaricom.com Attn: Joanne

Huari Duplexer/Diplexer List

Model	HRD-150	HRD-230	HRD-350	HRD-450
Frequency (MHZ)	136~155 147~180	220~240	330~390	380~512
Bandwidth (KHz)	±200	±500	±700	±500
Frequency Spacing (MHZ)	5.7	7	10	10
Insertion Loss (dB)	<1.0	<1.0	<1.0	<1.0
Isolation (dB)	>80	>80	>80	>80
Suppression (dB)	>80	>80	>80	>80
V.S.W.R	<1.5	<1.5	<1.5	<1.5
Nominal Impedance	50	50	50	50
Max.power Input (W)	30	30	30/50	30/50
Standard Termination	N	N	N	N
Dimension (mm)	214x154x31.5	214x154x31.5	275x154x31.5 275x191x39	223x154x31.5 223x191x39
Weight (KG)	1.2	0.9	1.2/2.0	1.2/2.0
Picture				