

	NU1100 
--	--

Access, Alarm, Bell, Time	
Access Control	✓
Alarm, Door Open	✓
Alarm, Duress	✓
Alarm, Tamper	✓
Authentication Method	Fingerprint, Password, EM Card (optional)
Authentication Text Message	✓
Authentication Voice Message	✓
Daylight Saving Time	N/A
Door Bell Button	✓
Time Bell	via Internal Speaker
Timezone Management	50 Groups
Audio, Operation Management, Power Management, Visual	
Backup Battery	N/A
Display Screen	122 x 32 LCD
Firmware Upgradeable	✓
Graphic Display Interface	✓
Image Display Interface	N/A
Keypad	17-Key
Language, Audio	Standard: English Optional: Any Other
Language, Display	Standard: English Optional: Any Other
Multi-Device Ready	Max. 255 units
On Screen Memory Capacity Check	✓
Operation Mode	Offline
Power Off, Auto	✓
Screen Saver	N/A
Self Testing	✓
Sleep Mode	✓
User Group Management	5 Groups
Voice Recording by User	N/A
Fingerprint, Memory Capacity, Smart Card	
False Acceptance Rate (FAR)	≤ 0.0001%
False Rejection Rate (FRR)	≤ 0.01%
Fingerprint Detection Area	16mm x 14 mm
Fingerprint Placement Angle	360°
Fingerprint Template Update	Auto
Fingerprint Verification	1:1, 1:N
Max. Capacity, Attendance Record	45,000
Max. Capacity, Identification	500
Max. Capacity, Management Record	1,000
Recognition Speed, Average	1.2 second
Smart Card Anti-Passback	✓
Data Transfer	
Access Control Interface	Relay Output, WG26 Input / Output
RS232	✓
RS485	✓
SD Card Slot	✓
TCP/IP	N/A
USB	1 x USB link to PC
Environmental Conditions, Power, Software	
Anti-Static Strength	< 15KV
Relative Humidity, Operation	20% to 60%
Relative Humidity, Storage	20% to 80%
Software	Free “UnionAttend”
Temperature, Operation	0°C to 45°C
Temperature, Storage	-10°C to 65°C
Voltage, Input	DC12V
Packing	
Dimensions (W x H x D)	70mm x 110mm x 30mm
Unit / Carton Box	10
Weight, Gross	757g
Weight, Net	290g