

产品定义	规格描述
Dimension 尺寸	188.53mm*89.11mm*158.62mm
Weight 产品重量	整机:262g
Chipset	zhognke8931H
Bluetooth Version	6
Frequency	2.4GHz, Class 2
Distance	15m
RF radiate RF	Onboard antenna
Sensitivity of receiving	-80dB/3M
ANC Noise Reduction Value	-40±3dB
Design Size(mm)	188.50mm*89.35mm*161.8mm
color	black
Total Weight	262g
Bluetooth version	V6.0 (HFP1.7、HSP1.2、HD Voice、Voice Prompts、A2DP1.3、AVRCP1.6、IOS BATTERY STATE MONITOR、Voice reporting、Multipoint)
Shutdown standby time	180D
Call time ANC OFF	102H
Call time ANC ON	71H
Standby time ANC OFF	863H
Standby time ANC ON	121H
Music playback time (50%volume) ANC OFF	146H
Music playback time (50%volume) ANC ON	84H
Music playback time (100%volume) ANC OFF	81H
Music playback time (100%volume) ANC ON	65H
Microphone	Electret microphone
Speaker	Dynamic Φ40mm
Headphone Battery	Polymer lithium battery specifications 103030 950mAh/3.7V
LED Indicator	The earphones have red and blue lights.
KEY	Physical buttons
Charging port	TYPE-C Charging port
Charging connector	TYPE-C Charging CABLE
Standby current ANC OFF	Typical : 0.88mA      MAX: 1.1mA
Standby current ANC ON	Typical : 7.3mA      MAX: 7.8mA
MP3current ANC OFF (50%volume)	Typical : 6.1mA      MAX: 6.5mA
MP3current ANC ON (50%volume)	Typical Value: 10.7mA      MAX:
MP3current ANC OFF (100%volume)	Typical : 10.2mA      MAX: 11.6mA
MP3current ANC ON (100%volume)	Typical : 14.1mA      MAX: 14.5mA
Talk current ANC OFF	Typical : 8.8mA      MAX: 9.3mA
Talk current ANC ON	Typical : 12.8mA      MAX: 13.2mA
Quiescent Current	Typical : 5.3uA      MAX: 6uA
Charging Current	Typical : 900mA      MAX: 950mA
Charging box input voltage	DC 5.0V 1A

Temperature Range	0-45°C
<b>Acoustic specifications :</b>	
Sensitivity	-32±2dB
Operating voltage :	1.5-3.6V
Frequency Response Range :	20Hz-40KHz
Output impedance :	200Ω
<b>Microphone Frequency Response curve</b>	
Dimension::	DynamicΦ40mm
Impedance :	32Ω±15%
Frequency response :	20mW
Power Maximum :	30mW
Noise Cancellation Depth:	-40±3dB