

Model:		
 		
Unit Weight	0.29kg	
Unit Size	90*85*162mm	
Carton size	44*38*34cm	
Qty	40pcs	
FCL weight	12.5kg	
Product function introduction		
• HD video quality, live stream, and watch recordings, wide viewing angle, see more of every moment • Intelligent Auto- Tracking, support remote viewing on iOS or Android • Support cloud storage for motion detected recordings, 2.4GHz WiFi wireless connection, no network cord required • Support local storage by MicroSD card up to 128GB • Support 2-way audio between phone and camera • Support 7X24H video recordings, never miss every moment		
Product specification		
System	pixel	2MP
	System structure	Embedded Linux real-time operating system
	Video processing	H.264 video encoding
Video	Image output	1920*1080@15fps
	Lens	3.6mm
	Shutter	Automatic shutter
	Pan/Tilt	355° left and right 65° up and down
	Day and night mode	IR-CUT infrared filter type
	Noise reduction	Support 2D/3D noise reduction
	Wide dynamic	Support digital wide dynamic
	Image flip	Support horizontal and vertical flip
Audio	Audio processing	G.711 codec standard, support audio and video synchronization
	Audio port	1 input, level 2Vp-p, impedance 1kΩ, support MIC/pickup input/output power
Storage Management	Recording mode	Manual recording, motion detection recording, timing recording
	Video storage	SD card storage/cloud storage
	Playback, backup	support
	Alarm trigger	Motion detection; push alarm information; support mobile phone
	Reset button	Support
Network	Wired network	Not support
	Wireless network	802.11b/g/n
	supporting agreement	Support NI protocol
Power	power supply	Power supply: DC5V/1.5A
	Reliability	Lightning protection: TVS 4000V lightning protection, anti-surge high temperature test is stable and reliable (including the whole)
Working Environment	Installation location	Homes, shops, schools, factories;
	Installation method	Lay flat, wall-mounted, hoisted
	Operating temperature	-10°C - + 55°C
	Working humidity	10%-90%
	Camera	1PCS
	Power Adapter	1PCS

Packing List	Data line	1PCS
	Screw pack	1PCS
	Manual	1PCS
	Mounting brackets	1PCS

n
t; 1 output, impedance 8Ω, 1W
ig, alarm recording
one, client remote monitoring,
je, anti-surge; 7*24 hours 65°C e machine test)
