


M12 B code male to male straight molded cable, unshielded/M12, B型公头直头对公头直头连接线, 不带屏蔽**Illustration/尺寸****Product photo/产品图****Part number/产品料号**

Pins/针数	Code/型	Part number("X" is length millimetre mm)/产品料号("X"表示长度, 单位毫米mm)		
		PVC jacket/PVC外被	PUR jacket/PUR外被	
5pins/5针	B code/B型	-10°C~+80°C	-40°C~+105°C	-40°C~+105°C
		12L00898-X	12L00899-X	12L00900-X

Pin assignment front view/针位分布前视图B code 5pins
B型5针**General data/常规数据**

Pins Numbers/针数	5pins/5针
Rated voltage/额定电压	60V
Rated current(40°C)/额定电流	4A
Standards/标准	IEC 61076-2-101
Termination/焊接方式	solder and over-mold/焊接和成型
Degree of protection/防护等级	IP67, IP68, IP69K
Wire gauge(mm²)/线规(平方数)	0.14mm²-0.75mm²
Wire gauge(AWG)/线号(平方数)	26AWG-18AWG
Mechanical operation/插拔次数	>100 mating cycles/大于100次
Contact resistance/接触电阻	≤5mΩ
Insulation resistance/绝缘电阻	≥100MΩ
Connector body/胶芯	TPU
Pins/端子	Brass with gold plated/黄铜镀金
Screw/螺丝	Brass with nickel plated/黄铜镀镍
Environmental compliance/环境符合标准	RoHs, Reach