

Model	LTB1004	
Tractor Parameters	Drive Type	4WD
	Overall Dimension(mm)	4230×1750×2820
	Min. operating weight(kg)	3250
	Rated traction force(N)	32010
	Wheel tread (front/rear)	1420/1352
	Wheel base(mm)	2070
	Min. ground clearance(mm)	400
	Min. Turning Radius(mm)	≤4.3
	Theoretical Speed(forward)	2.51~32.26
	Theoretical Speed(reverse)	2.20~28.27
Engine	Engine Model	Vertical, water cooled, four stroke, direct injection
Specification	Number of cylinders	4
	Engine Rated speed(r/min)	2400
	Engine Rated power (Kw)	73.5
Drive System	Clutch	Single,dry type,dual-function
	Gear box	4×3× (1+1)
	Main drive	Spiral bevel gearing
	Differential	Closed, 4 planeatry bevel gears
	Differential lock	Mechanical locking differential
	Final drive	Single planeatry gear
Traveling Mechanism	Tyre(front)	9.5-24
	Tyre(rear)	14.9-30
	Steering gear	Full hydraulic front wheel steering
	Brake	Wet type, disc brake
Working Device	PTO Speed (r/min)	540/760 or 540/1000
	PTO Spline Size	6 splines or 8 splines-φ38mm
	Max. lifting force(KN)	17640
	3-Point suspension	Category:II