

Application

Ordinary duty PVC cable for use in domestic appliances, kitchens and offices. For use with light portable appliances such as table lamps and office equipment. Generally unsuitable for outdoor use or industrial applications.

Technical Details

Cable Type: Flexible
 Conductor material: Copper
 Insulation/Sheath: PVC
 Temperature: 70°C maximum
 Voltage Rating: 450/750V
 Length: 100m in ring
 Color: White, Black, Gray



Model NO	Conductor		Insulation		Sheath		Weight
	Section (mm ²)	Max. Resistance at 20°C (MΩ/km)	Thickness (mm)	Max. Resistance at 70°C (MΩ/km)	Thickness (mm)	Overall OD (mm)	kg/km
LP-2G075	2×0.75	26	0.6	0.011	0.8	6.1	55
LP-2G100	2×1.0	19.5	0.6	0.01	0.8	6.5	60
LP-2G150	2×1.5	13.3	0.7	0.01	0.8	7.5	80
LP-2G250	2×2.5	7.98	0.8	0.009	1.0	9.0	119
LP-2G400	2×4.0	4.95	0.8	0.007	1.1	10.4	160
LP-3G075	3×0.75	26	0.6	0.011	0.8	6.5	65
LP-3G100	3×1.0	19.5	0.6	0.01	0.8	7.0	74
LP-3G150	3×1.5	13.3	0.7	0.01	0.8	8.1	101
LP-3G250	3×2.5	7.98	0.8	0.009	1.0	10.0	155
LP-3G400	3×4	4.95	0.8	0.007	1.1	11.3	250
LP-4G075	4×0.75	26	0.6	0.011	0.8	7.2	79
LP-4G100	4×1.0	19.5	0.6	0.01	0.8	7.9	94
LP-4G150	4×1.5	13.3	0.7	0.01	0.8	9.3	131
LP-4G250	4×2.5	7.98	0.8	0.009	1.0	10.8	185
LP-4G400	4×4.0	4.95	0.8	0.007	1.1	12.4	260
LP-5G075	5×0.75	26	0.6	0.011	0.8	8.2	95
LP-5G100	5×1.0	19.3	0.6	0.01	0.8	8.6	120
LP-5G150	5×1.5	13.3	0.7	0.01	0.8	10.2	164
LP-5G250	5×2.5	7.98	0.8	0.009	1.0	12.1	232
LP-5G400	5×4.0	4.95	0.8	0.007	1.1	14.0	330

SHENZHEN LANP CABLE LIMITED COMPANY

Address: NO.518, Jinbi Road, Biling Village, Pingshan Street, Pingshan District, Shenzhen, Guangdong, China

Tel : 0086-0755-8992-9897

Fax : 0086-0755-8992-9857

Web: www.lanp1.com