



Reputation Electronic Technology (HK) Co., Lt
Shenzhen World Reputation Electronic Technology Co., Ltd

Skype: rickpeng1989
Tel: +86 0755 29469669
Fax: +86 0755 29469669
Mobile: +86 18666204653

Web: <http://www.yumite.com.cn/en/>

ADD: Room B1213, Niulanqian Building, Minzhi Road, Longhua district, Shenzhen, China

Mould Number	YT200 Mini Laser Barcode Scanner Platform
Technical parameter	
Light Source Type	Visual lasing diode; the wave length is 650mm.
Trigger Mode	Manul and automatic optional
Scanning Mode	Single-line scanning
Scanning speed	100±2 times /s
Scan Precision	≥4mil
Printing Contrast Ratio	The lowest reflectivity difference is 30%.
Bit error rate	1/50 million
Environment Luminance	3000-12000Lux
Depth of field	5mm-630mm
Scanning angle	±60°±65°±42° (Left and right, front and back, rotation)
Decoding capacity	UPC/EAN/JAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, MSI, Code11 Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128Full ASCII Codabar, Code93, Discrete2of5, IATA, RSSvariants, Codabar, Chinese2of5, International general dimensional barcodes, e.g. Inteleaved2/5, Interleaved2of5 and China postal service code
Electrical parameter	
Input voltage	5VDC±0.25V
Power	250mW (Work): 325mW (momentary maximum)
Current	50mA (Work): 65mA (momentary maximum)
Standby current	<20mA
Prompt mode	Buzzer and LED indicator
Physical parameter	
Transfe cable interface	USB (standard): PS/2 and RS232 are selectable.
Dimensions	L*W*H: 70mm*50mm*22mm
Weight	58g (excluding cables)
Power Cable	Straight line, 1m
Interface type	RJ-45 crystal head
Outside material	ABS+PC
Environment parameter	
Temperature	0℃ to 50℃ (Work): -40℃ to 60℃ (storage)
Safety Regulations	Laser safety class: EN60825-1, Class 1, state level-I laser safety standard
	EMC: EN55022, EN55024
	Electrical safety: EN60950-1
	Packaging level: IP52
	Anti-knock capacity: This product can still work properly after falling down and being impacted on the concrete floor from the height of 3m for many times.

