

Goldensun LED Panel Lights Catalog--4

Model	Power	Picture		Parameter	Color Temperature	Carton Measurement & PCS/CTN
GT3030-20W	20W			Frame Material : 6063A Aluminum Base Plate : Galvanized Plate Parameter:Luminous Efficiency≥1600-2000lm/W CRI: Ra≥70 Engineering Size : 295*295*45mm N.W : 0.75 KG Integrating Size : 300*300*45mm N.W : 0.85 KG Working Temperature : -40°C--50°C Viewing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	20pcs/ctn
GT3060-24W	24W			Frame Material : 6063A Aluminum Base Plate: Galvanized Plate Driver: AC85-265V, 50/60Hz PF>0.5 Parameter:Luminous Efficiency≥1920-2400lm/W CRI: Ra≥70 Engineering Size : 595*295*45mm N.W : 1.5 KG Integrating Size : 300*600*45mm N.W : 1.6 KG Working Temperature : -40°C--50°C Viewing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	10pcs/ctn
GT6060-40W	40W			Frame Material : 6063A Aluminum Base Plate : Galvanized Plate Driver: AC85-265V, 50/60Hz PF>0.5 Parameter: Luminous Efficiency≥3200-4000lm/W CRI: Ra≥70 Engineering Size : 595*595*55mm N.W : 2.55 KG Integrating Size : 600*600*55mm N.W : 2.65 KG Working Temperature : -40°C--50°C Viewing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	66*14*66.5cm 2cps/ctn

GT6060-50W	50W			Frame Material : 6063A Aluminum Base Plate : Galvanized Plate Driver: AC85-265V, 50/60Hz PF>0.5 Parameter:Luminous Efficiency≥4000-5000lm/W CRI: Ra≥70 Engineering Size : 595*595*55mm N.W : 2.55 KG Integrating Size : 600*600*55mm N.W : 2.55 KG Working Temperature : -40°C--50°C Viewing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	66*14*66.5cm 2pcs/ctn
GT30120-50W	50W			Frame Material : 6063A Aluminum Base Plated : Galvanized Plate Driver: AC85-265V, 50/60Hz PF>0.5 Parameter: Luminous Efficiency≥1600-2000lm/W CRI: Ra≥70 Engineering Size : 295*1195*55mm N.W : 2.65 KG Integrating Size : 300*1200*55mm N.W : 2.75KG Working Temperature : -40°C--50°C Viweing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	2pcs/ctn
GT60120-85W	85W			Frame Material : 6063A Aluminum Base Plate : Galvanized Plate Driver: AC85-265V, 50/60Hz PF>0.5 Parameter: Luminous Efficiency≥1600-2000lm/W CRI: Ra≥70 Engineering Size : 595*1195*55mm N.W : 5.1 KG Integrating Size : 600*1200*55mm N.W : 5.3KG Working Temperature : -40°C--50°C Viewing Angle: 120° Warranty : 2 Years	3000K 4000K 6000K	2pcs/ctn