

NEWSMAY TECHNOLOGY CO.,LIMITED

Add: 4/F, Building A, Guangduoyao Innovation park, Dalang, Longhua New District, Shenzhen City
Tell: +86-755-89456786,email: barry.chan@newsmaytech.com

Model	S2-B560TPM
Picture	
Size	182* 179 * 37mm
CPU	Intel 11 th Gen, 10 th Gen socket Core i3,i5,i7, pentium/Celeron CPU, the CPU TDP 65W or 35W i3-10100 i5-10400/10500/11400/11500/ ---T i7-10700/11700/---T
Chipset group	Intel B560
Memory	2* SO-DIMM DDR4 , max 64GB
Storage	m.2 2280 SATA/NVME SSD 1 x 2.5"HDD /SSD
Graphics	Intel® UHD Graphics 730/750
Display Port	HDMI + DP + DP/HDMI option
Front I/O	1 x USB 3.2 GEN2 Type-C(10Gbps) 2 x USB3.2 Gen2 (10Gbps) 1 x Power button Line in(MIC) *1, Line out(Audio)*1
Rear I/O	HDMI + DP + HDMI/DP(can choose one of HDMI/DP) 1 x DC(19V4.74A or 19V6.15A) 1x RJ45(Gigabit LAN, Realtek 8111H) 2 x USB3.2 Gen 2 (10Gbps) 2 x USB3.0 1 x COM 1 x Combo(mic/audio)
Header on MB	2 x USB2.0 1 x COM232 1 x TPM(ASROCK TPM SPI 14-1 pin module)
AMIBIOS	WAKE ON LAN AUTO POWER ON RTC PXE
Wireless	m.2 PCIe Wi-Fi module port
VESA Mount	Support
LAN	RJ45 (Gigabit LAN)
Power Supply	DC 19V4.74A /19V6.15A