

Portable Printer HPP-76D

Feature

- Rechargeable Lithium Battery
- Original+1 Copy, 180X180dpi
- Can Print QR Code
- Better Connectivity With: WiFi / Bluetooth
- Charging Base: Standard

Specification

Printing Method	24 Dot Matrix
Printing Direction	Unidirectional or bidirectional printing
Resolution	180×180 DPI (Max.)
Print Speed	Max. 2.794 mm/s (19.8 lines/s)
Paper	Feed speed 100 mm/s (Max.)
Copy	Original+1 copy
Paper Type	Roll paper (normal paper, black mark paper, copy paper)
Paper Specifications	Roll paper model Common single-sheet roll paper
	Common two-sheet copy paper
	Width 57.5 ±0.5 mm, 76 ±0.5 mm
	Thickness Single-sheet roll paper: 0.06 ~ 0.085 mm
	Two-sheet copy paper (single sheet): 0.05 ~ 0.08 mm, total thickness ≤ 0.14 mm
	Diameter of paper: Max.: 40 mm
Printing Width	Max. 63.4 mm
Line Spacing	1/6inch, 1/8 inch, or by programmable in 1/360inch increments
Barcode	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, NW-7
Two-dimension Code	QR code, Chinese-sensible code
Emulation	ESC/PK2
Ribbon Model	JMR138 (can replace ribbon core JMR215)
Life	250000 characters
Cutting Method	Tear manually
Interface	This printer can be equipped with the following interfaces:
	USB interface (micro) + Wi-Fi (802.11b/g/n)
	USB interface (micro) + Bluetooth
Black Mark	Standard
Input Buffer	36 KB
Environmental Condition	Operating Environment Temperature: 5 ~ 35°C

	Humidity: 25 ~ 80%RH (No condensation)
	Storage environment Temperature: -40 ~ 55°C
	Humidity: ≤93%RH (40°C, No condensation)
Weight	Approx. 0.635 kg
Noise	<45 dB (A) (ISO7779 standard)
Control Panel	2 Keys and 5 LED indicators
Physical Dimensions	123 mm (Width) × 154 mm (Length) × 65 mm (Height)
Operate System	Windows XP/7/8/10; Android
Battery	7.4V, 2600mAh Chargeable lithium battery
AC Adapter	USB type C interface: DC 5V/2A
Energy Consumption	The printable length of 1time charge (25% print density) USB interface + Bluetooth≥35 meters; USB interface + Wi-Fi≥30 meters
	Maximum standby time USB interface + Bluetooth≥55 hours; USB interface + Wi-Fi≥35 hours

Picture



Shenzhen HCC Technology Co., Ltd.

 Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
 Post Code: 518057 Tel: 86-755-86655162 Fax: 86-755-8606-9640 Web: www.szhcct.com