

RoHS

NOTES:

CURRENT RATING(MAX.): 5AMPERES

DIELECTRIC WITHSTANDING VOLTAGE:1000V R.M.S

INSULATION RESESTANCE:5000 MEGOHMS AT DC 500V

CONTACT RESISTANCE(MAX.)30m chms

OPERATION TEMPERATURE:-55°~+105°

MATERIAL:

CONTACT: PHOSPHOR BRONZE

INSULATION:PBT+30%GLASS FIBER.UL 94V-0

SHELL;STEEL

POS.	DIM A	DIM B	DIM C	DIM D	DIM G
9	30.80	24.99	17.00	19.20	2.74
15	39.20	33.30	25.30	27.60	2.74
25	53.10	47.04	38.96	41.10	2.77
37	69.34	63.50	55.42	57.30	2.77

Ordering Information

HC-6235-02 M XX XX S X X 01

Connector
Type
F=Female
M=Male

No.of
Pins
15,26,
44,62P

Contact Plating
S0:Gold Flash/Tin
G0:Gold Flash
G3: 3U" Gold
G4: 5U" Gold

Color
B=Black
W=Whitie
U=Blue

Packing
T:Tube
A:Tray
O:Pe Bag

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Ayang

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

◆

HECON 东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-6235-02MXXXXSXX01

TITLE:

DB-XXP 公传统焊线式