



SHENZHEN LINWEAR INNOVATION TECHNOLOGY CO., LTD.

BT Call LA21 Smart Watch [APP: OnWear Pro] Color:Black



Mechanical

Water Resistance	Real IP68
Display Size	1.78"
Screen Type	AMOLED
Screen Cover	ON CELL, 2.5D Glass Cover
Middle Frame	Zinc alloy
Bottom Shell Material	PC+ Double Injection Mould
Wristband Material	Silicone
Body Size (L x W x H) mm	46*38*11.7

Hardware

MCU	Realtek8762EW
G SENSOR	stk8321,3axis G-sensor
PPG Heart rate sensor	HX3690Q
Screen	Capacitive full touch screen
Flash	RAM:578Kb+ROM 640Kb
Screen Resolution	368*448px
Bluetooth	BT3.0+BLE5.2, one click connection

Power

Working Voltage	3.8v
Battery Life	3~7Working Days, Standby 15 day
Battery Capacity	270mAh
Type of Battery	Polymer lithium battery
Charging Method	Magnetic charging
Charging Time	<2.5 hour

APP OS

iOS	IOS 11.0+
Android	Android6.0+

Function

Language-12	Chinese, English, German,Russian,Spanish,Portuguese,Japanese,Arabic,Italian, Hebrew,French
	Set on the watch
Calling function	BT calls
	Call records
	Contacts
Basic Functions	Clock, Date Display 12/24H
	Multi-watch face Online 100+ & DIY
	OTA upgrade
Entertainment function	BT music
	Voice assistant

Daily activity monitoring	Heart rate (each 10min)
	Blood oxygen
	Breathing Training
	Steps, Calories,Distance(Auto)
	Sleep monitor(Auto)
Exercise Functions 20	Walking
	Running
	Climbing
	Cycling
	Basketball
	Swimming
	Badminton
	football
	Elliptical
	yoga
	pingpong
	Rope skipping
	Free training
	tennis
	baseball
	Rugby
	hula hoop
	Golf
	long jump
	sit-ups
	Volleyball
Reminder	Incoming call
	SMS notification
	App push reminder
	Target reaching reminder
	Alarm
	Activity reminder
	Women's Health
	Drink water reminder
Others function	110+ Sports
	Remote camera control
	A-GPS
	Reset
	Weather forecast
	Stopwatch
	Always on display
	Restart
	Timer
	Music control
	Scan QR code to download
	Set the screen duration
	Firmware information
Gesture	Lift the wrist
	Lower the wrist
Environmental	
Working Temperature	-20°C to 50°C
Charge Temperature	0°C to 40°C
Working Humidity	10%-90%RH
Storage Temperature	-20°C to 60°C
Storage Humidity	5%-90%RH