

■ 产品说明：

- 额定温度: 120℃
- 参考标准: JASO D 608
- 导体使用绞合 0.5~8mm² 裸铜
- XLPE绝缘，符合 ROHS 环保标准
- 通过 JIS C 3406/1993 6.8 阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于汽车内部连接线

■ PRODUCT DESCRIPTION

- Rate temperature: 120℃
- Reference standard: JASO D 608
- Stranded, bare copper conductor 0.5~8mm²
- XLPE insulation, comply with ROHS environmental standard
- Passes JIS C 3406/1993 6.8 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For vehicle internal wiring of appliance



■ 产品结构 CABLE CONSTRUCTION

导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE Ω (/km,20℃)	耐压强度 DIELECTRIC STRENGTH V (AC, 1min)
面积 CROSS SECTION (mm ²)	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
0.5f	20/0.18	0.93	0.50	2.00	36.7	1000
0.5	7/0.32	0.96	0.50	2.00	32.7	1000
0.75f	30/0.18	1.14	0.50	2.20	24.4	1000
0.85	11/0.32	1.22	0.50	2.20	20.8	1000
1.25f	50/0.18	1.47	0.60	2.70	14.7	1000
1.25	16/0.32	1.48	0.60	2.70	14.3	1000
2	26/0.32	1.88	0.60	3.10	8.81	1000
3	41/0.32	2.36	0.70	3.80	5.59	1000
5	65/0.32	2.98	0.80	4.60	3.52	1000
8	50/0.45	3.67	0.80	5.30	2.32	1000