

SOS Button

Product Mode: R7052-V2 [2971371]



Packing

◆ Product Dimension	40*40*11.2 mm
◆ Net Weight	13.1g

Mechanical Specification

◆ Material	ABS
◆ Flame Retardance	UL94 V-0 750°C FIRE-PROOF
◆ Ingress Protection(IP)	IP20

Electrical Specification

◆ Power	CR2032 x 1 (included)
◆ Input Voltage	DC 3V
◆ Zigbee Module	ZTU
◆ Net Standard	IEEE 802.15.4/ZigBee
◆ Wireless Frequency	2.405-2.480GHz
◆ Battery Lifetime	1 Year (trigger frequency: 5 times a day)
◆ Connection Range (open area)	10~35 meters indoor and more than 70 meters in open air
◆ Working Temperature	-10°C ~+35°C
◆ Working Humidity	0 ~95%RH (non-condensing)

Software Function

◆ Battery Low	Yes
◆ Battery Level	Yes
◆ History Record	Yes
◆ Voice Support	\

Features

◆ Housing	White
◆ Button	Red
◆ Alarm LED	Red
◆ Power LED	Blue

Others

◆ Approved Certification	LVD:	RF:
	EN 62368-1:2014+A11:2017	ETSI EN 300 328 V2.2.2
	EMC:	Health:
	EN 55032:2015/A11:2020	EN 50663:2017
	EN 55035:2017/A11:2020	EN 62479:2010
	ETSI EN 301 489-1 V2.2.3	EN 62311:2008
	Draft ETSI EN 301 489-17 V3.2.2	
	EN 61000-3-2:2019	REACH:
	EN 61000-3-3:2013/A1:2019	(EC)1907/2006
	RoHS:	