TOGGLE SWITCH 18 SERIES

規　　格 RATING: 15A 125V AC, 10A 250V AC
接觸電阻 CONTACT RESISTANCE: 50M OHM MAX
絕緣電阻 INSULATION RESISTANCE: DC 500V 100M OHM MINI
耐 電 壓 DIELECTRIC STRENGTH: AC 1000V PER MINUTE
使用溫度 OPERATING TEMPERATURE: -20 C ~+68 C
電氣壽命 ELECTRICAL LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD

WTN-18-1213/2P2
SPDT 2P ON-OFF
SCREW TERMINAL



WTN-18-1213R1/2P2
SPST 2P ON-OFF
PC TERMINAL



WTN-18-1213/3P2
SPDT 3P ON-ON
SCREW TERMINAL



WTN-18-1213R1/3P3
SPDT 3P ON-OFF-ON
3P (ON)-OFF-ON
3P (ON)-OFF-(ON)
PC TERMINAL



WTN-18-1213/4P2
DPST 4P ON-OFF
SCREW TERMINAL




WTN-18-1213R1/3P2
SPDT 3P ON-ON
3P (ON)-OFF
PC TERMINAL




WTN-18-1213/3P3
SPDT 3P ON-OFF-ON
SCREW TERMINAL



WTN-18-1213R1/4P2
DPST 4P ON-OFF
PC TERMINAL



WTN-18-1213/6P2
DPDT 6P ON-ON
SCREW TERMINAL



WTN-18-1213R1/6P2
DPDT 6P ON-ON
PC TERMINAL



TOGGLE SWITCH 18 SERIES

WTN-18-1213/6P3
DPDT 6P ON-OFF-ON
SCREW TERMINAL



WTN-18-1213R1/6P3
DPDT 6P ON-OFF-ON
6P (ON)-OFF-ON
6P (ON)-OFF-(ON)
PC TERMINAL




WTN-18-1214/2P2
SPST 2P ON-OFF
CONTACT RATING: 125V 3A



WTN-18-1214/4P2
DPST 4P ON-OFF
CONTACT RATING: 125V 3A



WTN-18-1214/6P2
DPDT 6P ON-ON
CONTACT RATING: 125V 3A



WTN-18-1215
(A) DPDT 6P ON-ON
(B) DPDT 6P ON-OFF-ON
CONTACT RATING: 125V 10A



WTN-18-1216
SPDT 3P ON-ON
3P (ON)-ON
CONTACT RATING: 125V 5A 250V 2A/AC



WTN-18-1216R1
SPDT 3P ON-ON
CONTACT RATING: 125V 5A 250V 2A/AC



WTN-18-1217/6P
6 P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
SOLDER TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1217R1/6P
6P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
PC TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1217/9P
9P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
SOLDER TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC




WTN-18-1217R1/9P
9P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
PC TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC




TOGGLE SWITCH 18 SERIES

WTN-18-1217/12P
12P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
SOLDER TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1217R1/12P
12P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
PC TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1218/2P
2P MINI TOGGLE SWITCH
ON-OFF
SOLDER TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1218/3P
3P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
SOLDER TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1218/6P
6P MINI TOGGLE SWITCH
(A) 6P ON-ON
(B) 6P ON-OFF-ON
(C) 6P (ON)-OFF-ON
(D) 6P (ON)-OFF-(ON)
SOLDER TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1218R1/2P
2P MINI TOGGLE SWITCH
ON-OFF
PC TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1218R1/3P
3P MINI TOGGLE SWITCH
(A) ON-ON
(B) ON-OFF-ON
(C) (ON)-OFF-ON
(D) (ON)-OFF-(ON)
PC TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1218R1/4P
4P MINI TOGGLE SWITCH
ON-OFF
PC TERMINAL
CONTACT RATING:125V 5A
250V 2A/AC



WTN-18-1220
SUB-MINIATURE TOGGLE SWITCH
2P ON-OFF
CONTACT RATING: 3A 125V AC, 1A 250V AC
CONTACT RESISTANCE: 20M OHM MAX
INSULATION RESISTANCE: DC 500 100M OHM MINI
DIELECTRIC STRENGTH: AC 1000V PER MIN.
OPERATING TEMPERATURE: -20˚C~+65˚C
ELECTRICAL LIFE:
20000 MAKE AND BREAK CYCLES AT FULL LOAD




WTN-18-1221
SUB-MINIATURE TOGGLE SWITCH
3P ON-ON
CONTACT RATING: 3A 125V AC, 1A 250V AC
CONTACT RESISTANCE: 20M OHM MAX
INSULATION RESISTANCE: DC 500 100M OHM MINI
DIELECTRIC STRENGTH: AC 1000V PER MIN.
OPERATING TEMPERATURE: -20˚C~+65˚C
ELECTRICAL LIFE:
20000 MAKE AND BREAK CYCLES AT FULL LOAD



WTN-18-1222
SUB-MINIATURE TOGGLE SWITCH
6P ON-ON
CONTACT RATING: 3A 125V AC, 1A 250V AC
CONTACT RESISTANCE: 20M OHM MAX
INSULATION RESISTANCE: DC 500 100M OHM MINI
DIELECTRIC STRENGTH: AC 1000V PER MIN.
OPERATING TEMPERATURE: -20˚C~+65˚C
ELECTRICAL LIFE:
20000 MAKE AND BREAK CYCLES AT FULL LOAD



WTN-18-1225/2P2
PC TERMINAL, SPST
2P ON-OFF
RATING: 250V AC 15A
CONTACT RATING:50M OHM MAX
INSULATION RATING: DC 500V 100M OHM MIN.
DIELECTRIC STRENGTH: AC 1000V 1 MINUTE



TOGGLE SWITCH 18 SERIES

WTN-18-1225/3P2

PC TERMINAL, SPDT
3P ON-ON
RATING: 250V AC 15A
CONTACT RATING:50M OHM MAX
INSULATION RATING: DC 500V 100MOHM 1MIN.
DIELECTRIC STRENGTH: AC 1000V 1 MINUTE



WTN-18-1225/3P3

PC TERMINAL, SPDT
3P ON-OFF-ON
RATING: 250V AC 15A
CONTACT RATING:50M OHM MAX
INSULATION RATING: DC 500V 100M OHM MIN.
DIELECTRIC STRENGTH: AC 1000V 1 MINUTE



WTN-18-1225/4P2

PC TERMINAL, DPST
4P ON-OFF
RATING: 250V AC 15A
CONTACT RATING:50M OHM MAX
INSULATION RATING: DC 500V 100M OHM 1MIN.
DIELECTRIC STRENGTH: AC 1000V 1 MINUTE



WTN-18-1225/6P2

PC TERMINAL, DPDT
6P ON-ON
RATING: 250V AC 15A
CONTACT RATING:50M OHM MAX
INSULATION RATING: DC 500V 100M OHM 1MIN.
DIELECTRIC STRENGTH: AC 1000V 1 MINUTE



WTN-18-1225/6P3

PC TERMINAL, DPDT
6P ON-OFF-ON
RATING: 250V AC 15A
CONTACT RATING:50M OHM MAX
INSULATION RATING: DC 500V 100M OHM 1MIN.
DIELECTRIC STRENGTH: AC 1000V 1 MINUTE

