

Model	Picture	Specification	Plug	certification
XR-ODE5AC		UT:16A, 250V, 4000W **Overload Protector16A 179*52*30 (Plug Excluding) 3 X1.5mm², AC extended core, EU/KC, 1.5M/1.8M(optional)	EU/KR	CE, CB, KC, KCC
XR-EDE5AC		AC OUTPUT:16A, 250V, 4000W **Overload Protector16A 179*52*30 (AC cable Excluding) 3 X1.5mm², AC extended core, EU/KC, 1.5M/1.8M(optional)	EU/KR	CE, CB, KC, KCC
XR-ODE1A2C33 20W		AC OUTPUT 13A 250V, 3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+A1 Total:5V=3.6A, 18W SIZE:76mm*76mm*79mm	EU/KR	CE, VDE, CBKC, KCC, LVDERP, ROHS
XR-ODE1A2C33 30W		AC OUTPUT 16A 250V, 4000W DC OUTPUT USB-C1 / C2 + USB-A PDO 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20W=1.5A, 30W PPS:3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20W=1.5A, 30W C1+C2+A1 Total:5V=3.6A, 18W SIZE:76mm*76mm*79mm	EU/KR	CE, VDE, CBKC, KCC, LVDERP, ROHS
XR-EDE1A2C33 20W		AC OUTPUT 16A 250V, 4000W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+A1 Total:5V=3.6A, 18W 3 X 1.5mm², extended core 1.5m SIZE:76mm*76mm*79mm	EU/KR	CE, VDE, CBKC, KCC, LVDERP, ROHS
XR-EDE1A2C33 30W		AC OUTPUT 16A 250V, 4000W DC OUTPUT USB-C1/C2+USB-A PDO 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20W=1.5A, 30W PPS:3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20W=1.5A, 30W C1+C2+A Total:5V=3.6A, 18W 3 X1.5mm², AC extended core, EU/KC, 1.5M/1.8M(optional)**Overload Protector 16A	EU/KR	CE, VDE, CBKC, KCC, LVDERP, ROHS
XR-OUK1A2C33 20W		AC OUTPUT 13A 250V, 3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+A1 Total:5V=3.6A, 18W SIZE:76mm*76mm*79mm	UK	CB, CE, ROHS, REACH, ERP-TUV CNAS
XR-OUK1A2C33 30W		AC OUTPUT 13A 250V, 3250W DC OUTPUT USB-C1 / C2 + USB-A PDO 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20W=1.5A, 30W PPS:3.3V~11V=3.0A, 3.3V~16V=2.0A, 33W QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20W=1.5A, 30W C1+C2+A1 Total:5V=3.6A, 18W SIZE:76mm*76mm*79mm	UK	CB, CE, ROHS, REACH, ERP-TUV CNAS
XR-EUK1A2C33 20W		AC OUTPUT 13A 250V, 3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+A1 Total:5V=3.6A, 18W 3 X 1.5mm², extended core 1.5m SIZE:76mm*76mm*79mm	UK	CB, CE, ROHS, REACH, ERP-TUV CNAS

XR-EUK1A2C33 30W		AC OUTPUT 13A 250V, 3250W DC OUTPUT USB-C1/C2 +USB-A PDO 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20V=1.5A, 30W PPS: 3.3V-11V=3.0A, 3.3V-16V=2.0A, 33W QC 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20V=1.5A, 30W C+C2+A Total: 5V=3.6A, 18W 13A Overload protector	UK	CB, CE, ROHS, REACH, ERP-TUV CNAS
---------------------	---	--	----	--------------------------------------