

4G 4MP Solar PTZ Camera IP4-THS-452

Features:

- ◆ 4G PTZ Solar IP Camera.
- ◆ 4.0 Megapixel 2560*1440.
- ◆ 6pcs Array IR+White Light LED,30M.
- ◆ TF Card Max 128G,Two Way Audio.
- ◆ Built-in 5MP 3.6mm Fixed Lens.
- ◆ 5.0W Solar Panel.
- ◆ 4pcs 18650 Battery 8000mAh.
- ◆ IP66 Weatherproof Standard.
- ◆ Response Time:0.6S;Detection angle:110°.
- ◆ WIFI Signal:50M Outdoor,30M Indoor.



Key Feature:

- 4G Networking Connecting:QR Code.
- Recording Mode:Alarm/Manual.
- PIR Detection,Voice call,Remote waking,Motion Waking.
- Outdoor Bullet IP Camera.
- White Metal body with strong bracket.
- Built-in efficient antennas 4G.
- Panoramic Show:Analog 3D & Auto Cruise;.
- Support IR cut filter with auto switch.
- 4G wireless remote monitoring,support for all 4G SIM card.
- Support Dual-Stream technology.
- Two-way Audio(AAC&G.726 Coding):-38dB Mic /Inside 1W*Speaker.
- Support Micro SD/SDHC/SDXC card, the maximum up to128G.
- Support SMART IR, P2P and cross-browser access.
- Mobile APP Name: iCsee.
- 5.0W Solar Panel,4pcs 18650 Battery 8000mAh.
- Power:Solar Panel+USB Power DC 5V.
- Photographic distances:0-10Meters.
- Standby Time:15S,30S,60S optional.

4G Frequency Range:

- 1.Network Type: FDD-LTE TDD-LTE WCDMA/HSDPA/TD-SCDMA
EDGE/GPRS/EDGE
- 2.Frequency scope: LTE B1/B3/B8/B38/B39/B40/B41,TD-SCDMA B34/B39,WCDMA
2100M/900M GSM 900M/1800M (For EU and China)
- 3.Data rate: LTE FDD/TDD (CAT.4) DL:150Mbps UL:50Mbps

Product Advantages:

- Offer 3-Years Product Warranties.
- Logistics convenient.
- CE Certified.
- Strict product quality control.
- Easy installation.
- Lower price.

Product Applications:

This is the best product of safety field. It and hard disk video recorders,cable,power supply,display,etc. Constitute a complete security system. Its application is more extensive. Such as homes,factories,highways,office building,garden,community, or a large public places, etc.

Model No.	IP4-THS-452
Image Sensor	1/2.8" CMOS GK7202V200+SC2336
Resolution	4MP=2560*1440
Illumination	Color 0.06 Lux@F1.2(AGC on), B&W 0.08 Lux@F1.2(IR on)
Lens Mount	Built-in 5MP 3.6mm Fixed Lens
IRLED	Built-in 6pcs 850nm Array IR LED+White Light LED
IR Distance	30M (Night Vision)
System	PAL / NTSC
Resolution	Main Stream: 2560*1440@12FPS; Sub Stream: 800*448@25FPS;
Video Mode	HD/SD
Frame	4.0MP and below 25fps(50HZ)
Video Processing	H.265 video coding, support dual stream, AVI format; code stream 32~6144kpbs adjustable
	Support 3DNR,Support Digital WDR,Support JPEG Snapshot
Image Setting	Brightness, contrast, saturation, exposure, up and down inversion, left and right mirror adjustable
Audio	Built-in Microphone and Speaker
Audio Coding	G726,G711,AAC,MP3 format,8K sampling rate,support echo cancellation function
Network Protocol	TCP/IP,HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, IPv6, IPv4
Storage	TF Card (Max 128G)
Motion Detection	4 independent detection areas can be set (sensitivity 1-100 can be set)
Wake Up Mode	PIR+Motion Detect+Human Micro-Wave Detect(Radar),APP
Action with alarm	Send the alarm picture to the designated mailbox;
Intelligent Alarm	Radar Infrared Sensor alarm, effective distance of 10 meters
Sim Card	Support 2G/3G/4G
Type of network	FDD-LTE TDD-LTE WCDMA/HSDPA/TD-SCDMA EDGE/GPRS/EDGE
Operating Frequency	LTE B1/B3/B8/B38/B39/B40/B41,TD-SCDMA B34/B39,WCDMA 2100M/900M GSM 900M/1800M (For EU and China)
Speed	LTE FDD/TDD (CAT.4) DL:150Mbps UL:50Mbps
USIM/SIM	Micro SIM Card
AP	Yes
APP	iCsee
Function	Configure by WEB, OSD(on screen display),real-time video transmission, motion detection and IO alarm linkage ,center prompt and picture pop-up after

SHENZHEN JBE CCTV CO.,LTD

	IO alarm; support remote surveillance client software;support mobile monitoring(iOS, Android).
Solar Panel	5.0W Solar Panel
Battery	4pcs 18650 Battery 8000mAh
Photographic distance	0-10Meters
View Angle	92°
Induction range	0-10Meters
Detection angle	110°
S/N Ratio	>=50dB
ES	1/50 - 1/10,000S
White Balance	Auto Tracking White Balance
Gamma Ratio	>=0.45
Working Temp.	Outdoor: -10C to +60C
Humidity	0 to 95% RH (non-condensing)
Consumption	0.75W (work) 0.0025W (standby)
Real Standby	Built-in MCU, support true standby function, support infrared, key,Gpio alarm wake-up main system; system standby power consumption 60uA
Voltage Input	Power 5V DC 1A
Single Package	180*174*129 mm/0.87kg
18pcs/Carton	540*375*410 mm/16.4kg



SHENZHEN JBE CCTV CO.,LTD

5/F,Workshop Building A,Tozia Industrial Park,Lezhujiao,
Huangmabu Community,Xixiang Street,Bao'an District,Shenzhen,Guangdong,China
Email:Sales@jbecctv.cn Tel:+86 0755 23037680

www.jbecctv.cn