

POS Receipt Printer HCC-POS76IV (NEW)

Specification

Model No.		HCC-POS76IV (NEW)
Print	Printing Method	Dot Matrix
	Printing Speed	4.4 lines/s
	Resolution	42cpl-210(whole dot)/420(half dot)
	Effective Printing Width	76.2mm/57mm
Character	Character Set	ASCII, GB18030(Chinese)
	Print Font	Font A: 7x7 Font B:7x9Chinese: 16 x 16
	Character per Line	42/35
Paper Spec.	Paper Type	Plain paper
	Paper Width	76.0± 0.5mm/57.5± 0.5mm
	Paper Roll Diameter	Max: 85.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.05~0.08mm
Ribbon Cassette		ERC-39 Purple or Black
Paper Supply Method		Semi-auto paper loading
Printer Mechanism		Citizen Brand
Reliability	MCBF(MCBF)Mean Cycles	9 million lines
	Between Failure	
	TPH	9 million lines
Barcode		N/A
Emulation		ESC/POS
Driver		Windows98/2000/NT/XP/Vista/Win7/Win8/Linux/O POS
Sensor		Paper Near End Sensor/ Paper End Sensor Optional
Drawer Port		1 Port
Interface		RS-232/Parallel/USB/Ethernet
Power Supply (Adapter)		AC100 ~240V ± 10%(include) DC 24V, 1A
Auto cutter	Type	Guillotine
	Life	500,000 cuts
	Cutting Method	Partial cut
Physical	Net Weight	With cutter:1.9kg, without cutter:1.66kg
	Gross Weight	With cutter:3.3kg, without cutter:3.1kg
	Printer Dimension (WxLxH)	248x 154x 139 mm

	Color	Black
Environment	Operating Temp	0~ 50 °C
	Storage Temp	-20~60°C
	Operating Humidity	10~80%
	Storage Humidity	10~90%

Application

- Restaurants,
- Department Stores,
- Kitchen,
- Convenience Stores,
- HCCecialty Retail,
- Supermarket

Picture

