



S60B

LABEL PRINTER INTEGRATED HANDHELD TERMINAL

5.5-inch HD Durable large Display · High speed Octa- core · Android 9.0



Android



4G



WIFI



Bluetooth



Sticker print



1D barcode



2D barcode



NFC



Camera



GPS



Product parameters

Performance

CPU	Cortex-A53 Octa-core 64-bit 2.0GHz high-performance processor
RAM+ROM	2GB+16GB/4GB+64GB
Expand memory	Micro SD(TF) Supports up to 128GB
System	Android 9.0

Data communication

WLAN	Dual-band 2.4GHz/5GHz Supporting IEEE 802.11ac/a/b/g/n/d/e/h/i/j/k/r/v protocol
WWAN	2G: GSM(850/900/1800/1900MHz)
	3G: WCDMA(850/900/1900/2100MHz)
	4G: FDD(B1/B3/B4/B7/B8/B12/B20) TDD(B38/B39/B40/B41)
Bluetooth	Support Bluetooth 5.0+BLE Transmission distance 5-10 meters
GNSS	Support GPS, Galileo, Glonass, Beidou

Physical parameter

Dimensions	177mm x72mm x(23.7-48.8)mm
Weight	< 500g (Depends on device function configuration)
Display	5.5 inch display with resolution 720 x1440
TP	Supports multi-touch, etc.
Battery capacity	Rechargeable polymer battery 3.8V 5200mAh, removable
	Standby time > 350 hours
	Working time > 12 hours, Depending on usage and network environment
	Charging time 2-3 hours, Using standard power adapter and data cable
Camera	Rear camera: 13MP Support auto focus, Flash, etc.
	Front camera: 2MP
Expansion Card slot	Nano SIM card x1, TF card x1
Communication interface	Type-C USB x1, Support OTG function
Audio	Speaker (mono), Microphone, Receiver
Main keys	Home key, Delete key, Back key, Confirm key
Side keys	Power key, Volume +/- key, Scan key x2
Sensors	Gravity sensor, Light sensor, Proximity sensor, Vibration motor

Language/input method

Input	English, Pinyin, Handwriting input, Support soft keypad
Language	Language packs in Simplified Chinese, Traditional Chinese, English, Korean, Japanese, etc.

Data collection

Thermal sticker printer

Printing speed	70mm/s
Print points	384dots
Paper slot width	58mm
Paper slot diameter	35mm
Paper type	Support for Sticker / label Black mark printing

Barcode scanning (Optional)

2D Scanning engine	N6602, Honeywell N5703 N6703
1D Symbologies	Code128, EAN-13, EAN-8,Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, China post 25, ISBN/ISSN,Code93, UCC/EAN-128, GS1Databar,HIBC, etc.
2D Symbologies	PDF417, Micro PDF417, GS1 Composite, Aztec Code, Data Matrix, QR Code, Micro QR Code, Maxicode, Hanxin Code, etc.

NFC (Optional)

Frequency	13.56MHz
Protocol	Support ISO14443A/B, 15693 protocol
Distance	2cm-5cm

User environment

Operating temperature	-20℃ - 55℃
Storage temperature	-40℃ - 70℃
Environment humidity	5%RH - 95%RH(no condensation)
Drop specification	6 sides Supports 1.2 meters drops on the marble within the operating temperature
Rolling test	0.5m rolling for 6 sides, can still work steadily
Sealing	IP54

Accessories

Standard	Adapter x1, Data cable x1, Protective film x1, Instruction manual x1
Optional	Charging base, etc.

