



威固电子户外全彩系列产品规格书

OUTDOOR FULL COLOR SERIES PRODUCT SPECIFICATION



户外常规 P4-320 表贴三合一

OUTDOORCONVENTIONAL P4-320 SMD 3IN1 PRODUCT SPECIFICATION

产品规格书



户外全彩系列产品规格书

OUTDOOR FULL COLOR SERIES PRODUCT SPECIFICATION

模组 Unit Module	项目	Item	参数	Parameter
	产品型号	Model Number	VG-P4-10scan	
	模组尺寸	Module Size	320mm*160mm	
	物理点间距	Physical Pitch	4mm	
	物理密度	Physical Density	62500 dots/m2	
	发光点颜色	Pixel Configuration	1R1G1B	
	LED 封装	Package Mode	SMD 3IN1-1921	
	模组分辨率	Module Resolution	80dots (W)*40dots (H)	
	模组最大功耗	Max Power Consumption	40W	
	模组厚度	Module Thickness	15mm	
	模组重量	Module Weight	348g	
	驱动方式	Drive Type	恒流驱动 Constant drive	
	扫描方式	Scan Mode	1/10 扫描 1/10scan	
	接口方式	Port Type	HUB75	
	匹配箱体尺寸	Match Cabinet Size	W640mm*H640mm W960mm*H960mm W1120mm*1120mm	
	工作电压 (DC)	Working Voltage	DC 5V	
	防护措施	Protective Measures	三防漆 Three Proofing Paint	

户外全彩系列产品规格书

OUTDOOR FULL COLOR SERIES PRODUCT SPECIFICATION



户外全彩系列产品规格书

OUTDOOR FULL COLOR SERIES PRODUCT SPECIFICATION

显示屏参数 Display Parameters	最佳视角 Best Viewing Angle	H:160° ;V:120°
	视距 Recommended Viewing Distance	4m-35m
	驱动 IC Driver IC	北方集创 ICND 2037
	画面刷新率 Refresh Rate	3840Hz
	白平衡亮度 Brightness of White Balance	6000cd/m²
	输入电压 Input Voltage	110-220V;AC±10%
	工作温度/湿度 Operating Temperature/ Humidity	-30°C ~+45°C
	平均功耗 Average Power Consumption	350w/m²
	最大功耗 Max. Power Consumption	900w/m²
	寿命 Life Time	>100000 hours
	坏灯率 Bad Light Rate	<0.0001
	平均无故障时间 MTBF	>5000 hours

户外全彩系列产品规格书

OUTDOOR FULL COLOR SERIES PRODUCT SPECIFICATION

案例分享

CASE SHARING

