

Model				YSF-12CRN8	YSF-18CRN8	YSF-24CRN8	YSF-30CRN8
Nameplate Parameter	Rated Capacity	Cooling	W	3500(800-4100)	5300 (1300-5300)	7000(1800-7200)	8800(1800-9200)
	Rated Power Consumption	Cooling	W	1250(100-1900)	1760 (235-1900)	2300(440-2640)	2900(300-3500)
	Rated Running Current	Cooling	A	5.6(0.7-9.5)	8.5 (1.1-8.9)	10(2-12)	13.5(1.5-16)
	Max. Input Power		W	1900	1900	2.8	3900
	Max. Input Current		A	9.5	9	13	19
	EER Cooling		W/W	6.5	5.5	3.04	CSPF 6.0
	Power supply source		V/Ph/Hz	220V/60Hz	208-230V~/1/60Hz	220V~/60Hz	220/60
	Refrigerant			R32	R32	R32	R32
	Refrigerant Charged		g	470	690	750	1230
	Air Flow Volume		m3/h	600	850	1300	1300
	Indoor Noise level		dB (A)	43	47	50	50
	Outdoor Noise level		dB (A)	51	52	57	59
	Indoor unit weight (Net)		Kg	8	11	14	14
	Outdoor unit weight (Net)		Kg	21.5	23	38	42
Indoor unit configuration	Net Dimension (WxDxH)		mm	750×285×200	900×310×225	1082×330×233	1082×330×233
	Packing Dimension (WxDxH)		mm	800×345×265	970×382×302	1155×397×312	1155×397×312
Outdoor unit configuration	Compressor			SANYO	SANYO	SANYO	GMCC
	Net Dimension (WxDxH)		mm	705×279×530	709×285×535	825×655×310	900×700×350
	Packing Dimension (WxDxH)		mm	825×345×595	810×330×570	945×725×435	1020×770×430
Container Loading 40HC			Sets	255	225	155	145