


PIN	SYMBOL
1	VLED-
2	VLED+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	GND
32	HSYN
33	VSYN
34	DE
35	NC
36	GND
37	RESET
38	/CS
39	SCL
40	SDA

1. Display Mode:
2. Driving Condition:
3. Viewing Direction:
4. Operating Temp:
Storage Temp:
5. LCD:
6. IC:
7. Backlight:
8. Unspecified tolera
9. ROHS Request

5.0" TFT/TN
VDD=2.8~3.6V
ALL
-20~+70° C
-30~+80° C
TV上片细砂0.13, TV下片0.13光片
ST7701S
WHITE LED*12



深圳金视界光电科技有限公司
SHENZHEN GOLDEN VISION OPTOELECTRONIC CO., LIMITED

SCALE: 1/1	UNIT: mm	DATE	PAGE: 1/1		VER: V1.0
MODEL NO.:	GVH0500QH33S		APPROVE	CHECK	DESIGNER
PART NO.:					