

K319 Mobile Printer

- Industrial quality
- 50mm paper bin
- Adjustable paper width
- Bluetooth 4.0
- Support Windows / Android / iOS



Label printing

Gap detection and black mark detection allow printing of labels in different sizes

Printing features


High printing speed for text in various languages and graphics

Low energy Bluetooth

Supports multiple host connections

Long operating hours

2600mAh battery and highly optimized power management schemes ensure long operating hours without disruptions



Battery



Adapter



Data cable

SPECIFICATION

PRINTER SPECIFICATIONS

Printer Mode	Direct Thermal
Maximum Print Width	3"/72mm
Maximum Print Speed	70mm per second
Resolution	203dpi(8 dots/mm)
Print life	150km(25%Print density or the following)/Each point: 1.5million pulses
Power	19.76Wh(2600mAh)/7.4V Rechargeable lithium polymer battery
Character Sets	English, Russian, Arabic, Thai and other languages, and Chinese Japanese Korean characters, graphics, curve, pre-Storage Icon 1D bar-code: UPC-A, UPC-E, CODE39, EAN-13, EAN-8, CODEBAR, CODE128, CODE93, ITF 2D bar-code: QR Code, PDF417, DATAMATRIX
Programming Languages	ESC/POS CPCL(Compatibility)
Support System	Windows CE/Mobile Support Microsoft Standard SDK、API interface invocation(CE5.0 or above, Mobile5.0 or above) Android Support Google Standard SDK、API interface invocation(2.0 or above) IOS Support IOS System & Supply IOS SDK

MEDIA SPECIFICATIONS

Media width	42mm-80mm between any print width
Maximum Media Roll Size	50mm
Media Thickness	1.97~7.09mil
Media Type	Labels, Thermal paper

COMMUNICATION

Wired	Type	Type-C
Bluetooth	Bluetooth 2.1+4.0(BLE)	

PHYSICAL CHARACTERISTICS

Size(L*W*H)	109mm*107mm*55mm
Weight	354g

OTHERS

Charging interval	~2.5h
Stand-by time	180-200h
Prompt	Paper out prompt、Battery low prompt、Cover/opened prompt、Charging completed prompt、Printing、Communication mode
Display	OLED screen

ENVIRONMENT

Operating Temperature

Operating Temperature	Min	Max
	41°F(5℃)	+104°F(+40℃)
Operating humidity(Relatively)	20%	85%

Storage Temperature

Storage temperature	Min	Max
	-4°F(-20℃)	+158°F(+70℃)
Storage temperature (Relatively)	5%	95%